


A

B

C

D


Valve Adapter
WeatherPack 6 Pos.
Tower w/Sockets
A-N/A
B-N/A
C-Wht
D-Blk
E-Plug
F-Plug



45-05212
WR41664
Valve Adapter
DC: XX-XX

(36.00)



45-05212
WR41664
Valve Adapter
DC: XX/XX



Valve Adapter
WeatherPack 4 Pos.
Tower w/Sockets
A-N/A
B-Blk
C-Wht
D-N/A

Weatherpack Parts with Part #
Terminal Socket 18-20ga part # 12089188
Seal Green 18-20ga part # 12015323
Plug, Green part # 12010300
Tower, 6 position part # 12015799
Tower, 4 position part # 12015797

Note: 1.0 Cable: 2 Conductor, 18ga.
2.0 Description:
2.1 Conductors-Stranded Tinned Copper
2.2 Insulation-Color-Coded Polyvinylchloride
2.3 Jacket-Chrome Polyvinylchloride
Temperature Range: 105 deg. C
Voltage Rating: 300 Volts
UL Style 2464

MATERIAL:		N/A			
FINISH:		N/A			
PROJECTION:		SCALE: UNITS: X		DRAWN BY: <i>Bryan Reiser</i>	
		1:2		CHECKED BY: <i>Alan Redman</i>	
UNLESS OTHERWISE SPECIFIED TOLERANCE:		0-1" ±.1" X 1-5" ±.25" X 5-10" ±.5" X		APPROVED BY: <i>Dylan Stewart</i>	
10-60" ±.1" X 60-120" ±.2" X 120" ±.3" X		SHEET No: 1 of 1		DWG No: C-45-05212	
Midwest Technologies IL, LLC. Claims proprietary right in the material disclosed herein. This document is not to be used in any way detrimental to the interest of Midwest Technologies IL, LLC.					