

A


B

C

D

AMP 14-Pin Connector

Pos.	Color	Function
1	Red	Boom 1
2	Green	Boom 2
3	Brown	Boom 3
4	Black	Boom 4
5	White	Boom 5
6	Red	(+12v)
7	Black	Ground
8	Red	12vDC
9	Black	Ground
10	Blue	Open 12vDC
11	White	Closed 12vDC
12	Green	Ground
13	Orange	12vDC
14	Brown	Signal



WeatherPack 6 Pos Shroud

Pos	Color	Function
A	Red	12vDC
B	Black	Ground
C	Blue	Open 12vDC
D	White	Closed 12vDC
E	n/a	
F	n/a	

WeatherPack 3 Pos Tower

Pos	Color	Function
A	Green	Ground
B	Orange	12vDC
C	Brown	Signal

136.00

288.00

8.00

Boom 1

Boom 2

Boom 3

Boom 4

Boom 5

**All Booms (5)
WeatherPack
4 Pos Shroud**

Pos	Color	Function
A	Black	Ground
B	n/a	
C	White	Signal
D	Red	(+12v)

Notes: 1.0 All dimensions are displayed in "Inches", Unless otherwise specified.

MATERIAL:		N/A			
FINISH:		N/A			
PROJECTION:		SCALE: UNITS: X		TITLE:	
UNLESS OTHERWISE SPECIFIED TOLERANCE:		1:4		Harness, Flow Control Willmar 8000 Series	
REV. DATE		NO. No		DRAWN BY: <i>Bryan Reiser</i>	
R0 1/30/03 010081		0-1" +/- .1" N/A 10-60" +/- 1" N/A XX N/A		CHECKED BY: <i>Andy Neuberger</i>	
		1-5" +/- .25" N/A 60-120" +/- 2" N/A XXX N/A		APPROVED BY: <i>Andy Neuberger</i>	
		5-10" +/- .5" N/A 120" +/- 3" N/A < N/A		SHEET No: DWG No:	
				1 of 1 C-45-10007	
Midwest Technologies IL, LLC. Claims proprietary right in the material disclosed hereon. This document is not to be used in any way detrimental to the interest of Midwest Technologies IL, LLC.					