

A

B

C


D

1

2

3

4



Plug, 28 Pos. Skt Framatome

- A-Grn/Blk/Wht
- B-Red/Blk/Wht
- C-Wht/Blk/Red
- D-Blk/Wht/Red
- E-Orn/Grn
- F-Red/Grn
- G-Blu/Red
- H-Orn/Red
- J-Wht/Red
- K-Blk/Red
- L-Blu/Wht
- M-N.C.
- N-Red/Wht
- P-Blk/Wht
- R-Blu/Blk
- S-Orn/Blk
- T-Grn/Blk
- U-Grn/Wht
- V-Red/Blk
- W-Wht
- X-Wht/Blk
- Y-N.C.
- Z-N.C.
- a-Orn
- b-Grn
- c-Blu
- d-Blk
- e-Red

Receptacle 28 pos. Pin Framatome

- A-Grn/Blk/Wht
- B-Red/Blk/Wht
- C-Wht/Blk/Red
- D-Blk/Wht/Red
- E-Orn/Grn
- F-Red/Grn
- G-Blu/Red
- H-Orn/Red
- J-Wht/Red
- K-Blk/Red
- L-Blu/Wht
- M-N.C.
- N-Red/Wht
- P-Blk/Wht
- R-Blu/Blk
- S-Orn/Blk
- T-Grn/Blk
- U-Grn/Wht
- V-Red/Blk
- W-Wht
- X-Wht/Blk
- Y-N.C.
- Z-N.C.
- a-Orn
- b-Grn
- c-Blu
- d-Blk
- e-Red

NOTES:

1.0 CABLE:

CABLE, 18 CONDUCTOR, 25GA.
 DESCRIPTION:
 CONDUCTORS: STRANDED TINNED COPPER
 INSULATION: COLOR-CODED POLYVINY LCHLORIDE
 CONSTRUCTION: CONDUCTORS ARE CABLED
 JACKET: CHROME POLYVINY LCHORIDE
 TEMPERATURE RANGE: 10 5 deg. C
 VOLTAGE RATING: 300 VOLTS
 UL STYLE 2464

MATERIAL: N/A		Midwest Technologies Illinois	
FINISH: N/A		TITLE: 48297-S5-7 Cable, Main Ext., 7 Meter	
PROJECTION:	SCALE: UNITS: X INCH METRIC: 1:4	DRAWN BY: Bryan Reeves	
UNLESS OTHERWISE SPECIFIED TOLERANCE:		CHECKED BY: Bryan Reeves	
R0	7/17/02	010128	1 of 1
REV.	DATE	DWG No.	C-45-20242
Midwest Technologies IL, LLC. Claims proprietary right in the material disclosed hereon. This document is not to be used in any way detrimental to the interest of Midwest Technologies IL, LLC.			