



ITEM NO.	PART NO.	DESCRIPTION
1A*	58430-5-433EC-2-D	430 BALL VALVE MANIFOLD, 2-WAY, 3 SECTIONS WITH BOLTED FLANGE CONNECTION
1B*	58570-5-433EC-3FB-D	430 BALL VALVE MANIFOLD, FLOWBACK, 3 SECTIONS WITH BOLTED FLANGE CONNECTION
1C*	58580-1-433EC-3-D	430 BALL VALVE MANIFOLD, 3-WAY, 3 SECTIONS WITH BOLTED FLANGE CONNECTION
1.1	CP98496-PP	MALE BOLTED INLET ADAPTER, POLYPROPYLENE (BLACK)
2	CP37553-25-SS	M6X1X25MM METRIC HEX HEAD CAP SCREW, STAINLESS STEEL (4 REQ'D PER CONNECTION)
3	CP45520-SS	M6 LOCK WASHER, STAINLESS STEEL (4 REQ'D PER CONNECTION)
4	CP55212-SS	M6X1MM HEX NUT, STAINLESS STEEL (4 REQ'D PER CONNECTION)
5	CP7717-2/222-VI	O-RING, VITON (1 REQ'D PER CONNECTION)
6	98510-PP	98510 PRESSURE RELIEF VALVE WITH BOLTED FLANGE CONNECTION, POLYPROPYLENE
7	CP98498-SS	430 ACCESSORY MOUNTING BRACKET, STAINLESS STEEL
8	CP98497-PP	MALE LARGE QUICK CONNECT BY BOLTED FLANGE CONNECTION, POLYPROPYLENE (BLACK)
AB98499-KIT, 430 ACCESSORY MOUNTING KIT INCLUDES ITEMS 2-5		
*430 BALL VALVES WITH BOLTED FLANGE CONNECTION AVAILABLE IN 1-9 SECTIONS		

FOR ADDITIONAL COMPONENT DETAILS & OPTIONS PLEASE SEE

*ADDITIONAL 430 MANIFOLD ASSEMBLIES - DS98600, PL98600-A, PL98600-B

*PRESSURE RELIEF VALVE - DS98510, DS98510X2, DS98510X2M, PL98510

VITON® IS A TRADEMARK OF DUPONT COMPANY

MOUNTING NOTE: WHEN USING THE MOUNTING BRACKET, THE BOTTOM TWO BOLTS DO NOT REQUIRE LOCK WASHERS (ITEM 3).

DESCRIPTION:

**98600, 98601, 98602 SERIES
430 MANIFOLD BALL VALVES
98600, 98601, 98602 SERIES
RELIEF VALVE**



Spraying Systems Co.®
Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60187-7901

REVISION NO. 1	PARTS LIST PL98600-A
REFERENCE: 10/18/2011	SHEET: 1 OF 1 DWG SIZE: B