



SECTIONAL VIEW

* **NOTE:** CHECK VALVE
11750-PP DOES NOT
REQUIRE SNAP RING

CHECK VALVE NO.	BODY MATERIAL	SPRING RETAINER MATERIAL
11750	BRASS	STAINLESS STEEL
11750-AL	ALUMINUM	STAINLESS STEEL
11750-SS	STAINLESS STEEL	STAINLESS STEEL
11750-PP	POLYPROPYLENE (BLACK)	POLYPROPYLENE (BLACK)

SUPPLIED AS STANDARD WITH 5 P.S.I SPRING,
ON REQUEST 10 AND 20 PSI SPRINGS ARE ALSO AVAILABLE.
ALL OTHER COMPONENTS ARE STAINLESS STEEL.

THE NO. 11750 LARGE FLOW CHECK VALVE PREVENTS DRIPPING FROM
NOZZLES - AFTER THE LINE PRESSURE IS SHUT OFF. THIS CHECK
VALVE CAN BE USED WITH ALL TYPE T, TT, TD, #7421 SPLIT-EYELET,
#111 AND #112 VARI-SPACING NOZZLES.

IT CAN BE USED WITH THE INTERCHANGEABLE FLAT SPRAY, HOLLOW CONE
SPRAY, FULL CONE SPRAY, AND SOLID STREAM TIPS - AS WELL AS THE
DISC AND CORE TIP ASSEMBLIES. RECOMMENDED FOR CAPACITIES FROM
APPROX. 0.4 TO 1.5 GPM. FOR LOWER CAPACITIES, USE THE #4193
CHECK VALVE-STRAINER AS SHOWN ON DATA SHEET 4193.

DESCRIPTION:
NO. 11750 LARGE FLOW
CHECK VALVE



Spraying Systems Co.[®]

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No. 3

Data Sheet No.

11750

Ref.

SHEET OF