



MAX. RECOMMENDED PRESSURE 75 PSI (5 bar)^o AT TEMP. 100 F (38 C):

STRAINER No.	PIPE CONN. (F)	STRAINER HEAD MATERIAL	SCREENS				NET WEIGHT	FLOW RATE WITH 5 PSI (0.35 bar) PRESSURE DROP
			MESH SIZE	OPENING	COLOR CODE	FULL AREA		
AA124A-3/4-PP	3/4" NPT	POLYPROPYLENE	16	.045" (1.1 mm)	GRAY	17 SQ. IN. (109 cm ²)	7 oz. (0.20 kg)	23 GPM (87 l/min)
AAB124A-3/4-PP	3/4" BSPT	POLYPROPYLENE	30	.021" (0.53 mm)	YELLOW			34 GPM (129 l/min)
AA124A-1-PP	1" NPT	POLYPROPYLENE	50	.011" (0.28 mm)	RED			
AAB124A-1-PP	1" BSPT	POLYPROPYLENE	80	.007" (0.18 mm)	BLUE			

DESCRIPTION:

NO. AA124A-3/4-PP AND
NO. AA124A-1-PP
LIQUID STRAINERS



Spraying Systems Co.[®]

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1

Ref.

Data Sheet No.

124A-PP

SHEET OF