



MATERIAL: STAINLESS STEEL

1/4 TTG-SS-W NOZZLE SHOWN.  
ALSO AVAILABLE WITH  
1/4 N.P.T. (F) INLET CONN. AS 1/4 TTG-SS-W

TEEJET NOZZLE NO.	SPRAY TIP NO.	LIQUID PRESSURE IN P.S.I.	CAPACITY IN G.P.M.	GALLONS PER ACRE			
				4 MPH	5 MPH	6 MPH	7.5 MPH
1/4 TTG-SS2.8W	TG-SS-2.8W	15	.34	12.4	9.9	8.3	6.6
		20	.38	14.1	11.3	9.4	7.5
		25	.42	15.6	12.5	10.4	8.3
		30	.45	16.9	13.5	11.2	9.0
		40	.52	19.1	15.3	12.6	10.2
1/4 TTG-SS4.3W	TG-SS-4.3W	15	.51	19.1	15.3	12.7	10.2
		20	.58	22.2	17.3	14.4	11.6
		25	.64	24.4	19.1	15.4	12.7
		30	.70	26.6	21	17.3	13.8
		40	.79	29.9	24	19.6	15.7
1/4 TTG-SS5.6W	TG-SS-5.6W	15	.67	22.5	19.9	16.6	13.3
		20	.76	25.8	22.3	18.3	15.0
		25	.84	29.1	25.5	21.1	16.8
		30	.91	32.4	27.7	22.8	18.0
		40	1.0	36	31	26	20
1/4 TTG-SS8W	TG-SS-8W	15	.96	36	28	24	18.9
		20	1.1	40	32	27	21
		25	1.2	44	36	30	24
		30	1.3	48	39	32	26
		40	1.5	55	44	36	29
1/4 TTG-SS10W	TG-SS-10W	15	1.2	44	36	30	24
		20	1.4	50	40	34	27
		25	1.5	55	44	37	30
		30	1.6	60	48	40	32
		40	1.8	68	55	46	36
1/4 TTG-SS12W	TG-SS-12W	15	1.4	53	43	36	28
		20	1.6	60	48	40	32
		25	1.8	67	53	44	36
		30	1.9	72	58	48	39
		40	2.2	82	66	55	44
1/4 TTG-SS14W	TG-SS-14W	15	1.7	62	50	41	33
		20	1.9	70	56	47	37
		25	2.1	78	62	52	41
		30	2.3	84	67	56	45
		40	2.6	95	76	64	51

TABULATION IS BASED ON WATER AT TEMPERATURE OF 70°F.

**DESCRIPTION:**

GALLONS PER ACRE  
 1/4TTG-SS-W  
 TEEJET NOZZLES  
 (40° SPACING)



**Spraying Systems Co.®**

Spray Nozzles and Accessories  
 P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Data Sheet No.

**17176**

Ref.

SHEET OF