



TEEJET FLAT SPRAY TIP NO.	LIQUID PRESSURE IN P.S.I.	CAPACITY 1- NOZZLE IN G.P.M.	GALLONS PER 1000 SQ. FT.					
			2 M.P.H.	3 M.P.H.	4 M.P.H.	5 M.P.H.	7.5 M.P.H.	10 M.P.H.
6501	20	.07	.24	.16	.12	.10	—	—
	30	.09	.30	.20	.15	.12	—	—
	40	.10	.34	.23	.17	.14	—	—
	50	.11	.38	.25	.19	.15	.10	—
8001	60	.12	.42	.28	.21	.17	.11	—
	20	.14	.48	.32	.24	.19	.13	.10
	30	.17	.59	.39	.30	.24	.16	.12
	40	.20	.66	.45	.34	.27	.18	.14
6502	50	.23	.76	.51	.38	.30	.20	.15
	60	.25	.84	.56	.42	.33	.22	.17
	20	.21	.72	.48	.36	.29	.19	.14
	30	.26	.89	.59	.44	.35	.24	.18
6503	40	.30	1.0	.68	.51	.41	.27	.20
	50	.34	1.1	.76	.57	.46	.30	.23
	60	.37	1.3	.84	.63	.50	.33	.25
	20	.28	.96	.64	.48	.39	.26	.19
6504	30	.35	1.2	.79	.58	.47	.31	.24
	40	.40	1.4	.91	.68	.55	.36	.27
	50	.44	1.5	1.0	.76	.61	.41	.30
	60	.49	1.7	1.1	.84	.67	.45	.33
6505	20	.35	1.2	.80	.60	.48	.32	.24
	30	.43	1.5	.98	.74	.59	.39	.30
	40	.50	1.7	1.1	.85	.68	.45	.34
	50	.56	1.9	1.3	.95	.76	.51	.38
8005	60	.61	2.1	1.4	1.0	.84	.56	.42
	20	.42	1.4	.96	.72	.58	.39	.29
	30	.52	1.8	1.2	.89	.71	.47	.35
	40	.60	2.0	1.4	1.0	.82	.55	.41
6506	50	.67	2.3	1.5	1.1	.91	.61	.46
	60	.73	2.5	1.7	1.3	1.0	.67	.50
	20	.56	1.9	1.3	.96	.77	.51	.39
	30	.69	2.4	1.6	1.2	.94	.63	.47
6508	40	.80	2.7	1.8	1.4	1.1	.73	.55
	50	.89	3.0	2.0	1.5	1.2	.81	.61
	60	.98	3.3	2.2	1.7	1.3	.89	.67
	20	.70	2.4	1.6	1.2	1.0	.64	.48
6510	30	.86	3.0	2.0	1.5	1.2	.79	.59
	40	1.0	3.4	2.3	1.7	1.4	.91	.68
	50	1.1	3.8	2.5	1.9	1.5	1.0	.76
	60	1.22	4.2	2.8	2.1	1.7	1.1	.84

TABULATION IS BASED ON SPRAYING WATER AT TEMPERATURE OF 70°F.

DESCRIPTION:

GALLONS PER 1000 SQ. FT.
USING 65 DEG. AND
80 DEG. SERIES
TEEJET SPRAY TIPS
-20 IN. SPACING-



Spraying Systems Co.[®]

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Data Sheet No.

18979-1

Ref.

SHEET OF