



TEEJET FLAT SPRAY TIP NO.	LIQUID PRESSURE IN P.S.I.	CAPACITY 1-NOZZLE IN G.P.M.	GALLONS PER 1000 SQ. FT.					
			2 M.P.H.	3 M.P.H.	4 M.P.H.	5 M.P.H.	7.5 M.P.H.	10 M.P.H.
6501	20	.07	.48	.32	.24	.19	.13	.10
	30	.09	.59	.39	.30	.24	.16	.12
	40	.10	.68	.45	.34	.27	.18	.14
	50	.11	.76	.51	.38	.30	.20	.15
	60	.12	.84	.56	.42	.33	.22	.17
8001	20	.14	.96	.64	.48	.39	.26	.19
	30	.17	1.2	.79	.59	.47	.31	.24
	40	.20	1.4	.91	.68	.55	.36	.27
	50	.23	1.5	1.0	.76	.61	.41	.30
	60	.25	1.7	1.1	.84	.67	.45	.33
6502	20	.21	1.4	.96	.72	.58	.39	.29
	30	.26	1.8	1.2	.89	.71	.47	.35
	40	.30	2.0	1.4	1.0	.82	.55	.41
	50	.34	2.3	1.5	1.1	.91	.61	.46
	60	.37	2.5	1.7	1.3	1.0	.67	.50
8002	20	.28	1.9	1.3	.96	.77	.51	.39
	30	.35	2.4	1.6	1.2	.94	.63	.47
	40	.40	2.7	1.8	1.4	1.1	.73	.55
	50	.44	3.0	2.0	1.5	1.2	.81	.61
	60	.49	3.3	2.2	1.7	1.3	.89	.67
6503	20	.35	2.4	1.6	1.2	.96	.64	.48
	30	.43	3.0	2.0	1.5	1.2	.79	.59
	40	.50	3.4	2.3	1.7	1.4	.91	.68
	50	.56	3.8	2.5	1.9	1.5	1.0	.76
	60	.61	4.2	2.8	2.1	1.7	1.1	.84
8003	20	.42	2.9	1.9	1.4	1.2	.77	.58
	30	.52	3.5	2.4	1.8	1.4	.94	.71
	40	.60	4.1	2.7	2.0	1.6	1.1	.82
	50	.67	4.6	3.0	2.3	1.8	1.2	.91
	60	.73	5.0	3.3	2.5	2.0	1.3	1.0
6504	20	.56	3.9	2.6	1.9	1.5	1.0	.77
	30	.69	4.7	3.1	2.4	1.9	1.3	.94
	40	.80	5.5	3.6	2.7	2.2	1.5	1.1
	50	.89	6.1	4.1	3.0	2.4	1.6	1.2
	60	.98	6.7	4.5	3.3	2.7	1.8	1.3
8004	20	.70	4.8	3.2	2.4	1.9	1.3	.96
	30	.86	5.9	3.9	3.0	2.4	1.6	1.2
	40	1.0	6.8	4.5	3.4	2.7	1.8	1.4
	50	1.11	7.6	5.1	3.8	3.0	2.0	1.5
	60	1.22	8.4	5.6	4.2	3.3	2.2	1.7

TABULATION IS BASED ON SPRAYING WATER AT TEMPERATURE OF 70°F.

DESCRIPTION:

GALLONS PER 1000 SQ. FT.
USING 65 DEG. AND
80 DEG. SERIES
TEEJET SPRAY TIPS
-10 IN. SPACING-



Spraying Systems Co.®

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Data Sheet No.

18979

Ref.

SHEET OF