



QUICK TEEJET® CAP WITH GROOVES THAT FIT LOCATING LUGS OF BODY - CELCON. YELLOW COLOR STANDARD. (OTHER COLORS OPTIONAL)

TEEJET SPRAY TIP - FLAT SPRAY PATTERN AUTOMATICALLY POSITIONED AT 15° ANGLE FROM BODY FLATS.

U.S. PATENT No.'S, 4527745, D280125, OTHER U.S. AND FOREIGN PATENTS GRANTED OR PENDING.

OTHER FEATURES:

- QUICK CHANGE OF INTERCHANGEABLE TEEJET®, FLOODJET® AND CONEJET® TIPS... AS WELL AS DISC-CORE COMBINATIONS.
- DRIP-FREE POSITIVE SHUT-OFF.
- MADE OF CORROSION RESISTANT MATERIALS.
- No. CP19438-EPR SEAT GASKET MADE OF EPDM. No. CP19438-VI VITON® OPTIONAL.
- STANDARD DIAPHRAGM IS EPDM. VITON AND TEFLON® DIAPHRAGM OPTIONAL
- OPENING PRESSURE - 10 PSI (0.7 bar)
- MAXIMUM OPERATING PRESSURE - 300 PSI (20 bar).
- LOW PRESSURE DROP: 3.9 PSI AT 2 GPM (.27 bar AT 7.6 l/min)

HOW TO ORDER:

FOR DIAPHRAGM QUICK TEEJET BODY ASB. ONLY (LESS CAP, SEAT GASKET, TIP & STRAINER: SPECIFY BODY ASSEMBLY No.

EXAMPLE: QJ8360-NYB DIAPHRAGM QUICK TEEJET NOZZLE BODY ASSEMBLY

DESCRIPTION:
NO. QJ8360-NYB DIAPHRAGM QUICK TEEJET® NOZZLE BODY ASSEMBLIES



Spraying Systems Co.®
 Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 8
 Ref.

Data Sheet No.
19520
 SHEET OF