



QUICK TEEJET® CAP WITH GROOVES THAT FIT LOCATING LUGS OF BODY - CELCON.

U.S. PATENT No.'S, 4527745, D280125, OTHER U.S. AND FOREIGN PATENTS GRANTED OR PENDING.

TO INSTALL ASSEMBLY DRILL 3/8" (9.5 mm) HOLE IN PIPE, DEBURR, THEN INSERT SPLIT-EYELET INLET AND CLAMP ASSEMBLY IN PLACE

OTHER FEATURES:

- FAST AND EASY WAY TO MOUNT SPRAY NOZZLES TO A BOOM.
 - QUICK CHANGE OF INTERCHANGEABLE TEEJET®, FLOODJET® AND CONEJET® TIPS... AS WELL AS DISC-CORE COMBINATIONS.
 - MADE OF CORROSION RESISTANT MATERIALS.
 - STANDARD O'RING IS BUNA-N. VITON® OPTIONAL.
 - No. CP19438-EPR SEAT GASKET MADE OF EPDM. No. CP19438-VI VITON® OPTIONAL.
 - MAXIMUM OPERATING PRESSURE - 300 PSI (20 bar).
 - OPENING PRESSURE - 10 PSI (0.7 bar)
- QJ20036-- SPLIT-EYELET QUICK TEEJET NOZZLES ARE SUPPLIED COMPLETE WITH NOZZLE BODY, QUICK TEEJET CAP, AND SEAT GASKET... TOGETHER WITH SPRAY TIP (AND STRAINER IF RECOMMENDED FOR TIP SIZE).

HOW TO ORDER:

FOR SPLIT-EYELET QUICK TEEJET BODY ASB. ONLY (LESS CAP, SEAT GASKET, TIP & STRAINER): SPECIFY BODY ASSEMBLY No.

EXAMPLE: QJ20036-1/2-NYB SPLIT-EYELET QUICK TEEJET BODY ASSEMBLY

FOR COMPLETE NOZZLE: SPECIFY THE BODY ASB. No., SPRAY TIP No., MATERIAL.

EXAMPLES: QJ20036-1/2-NYB+8002-SS SPLIT-EYELET QUICK TEEJET NOZZLE WITH STAINLESS STEEL TIP
 QJ20036-1/2-NYB+TK-2 SPLIT-EYELET QUICK TEEJET NOZZLE WITH BRASS FLOODJET TIP

BODY ASSEMBLY No.	"A" APPROX.	"B"	TO CLAMP ON
QJ20036-1/2-NYB	2 19/32" (66 mm)	1 3/16" (30 mm)	1/2" PIPE, 13/16" & 7/8" O.D. TUBINGS (20-22 mm O.D.)
QJ20036-3/4-NYB	2 13/16" (71 mm)	1 3/16" (30 mm)	3/4" PIPE, 1" & 1 1/16" O.D. TUBINGS (25-27 mm O.D.)

DESCRIPTION:
 NO. QJ20036--NYB SPLIT-EYELET
 QUICK TEEJET® NOZZLE
 BODY ASSEMBLY



Spraying Systems Co.®
 Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 2
 Ref.

Data Sheet No.
 20389
 SHEET OF