



LENGTH - 8 5/16 (211 mm)
 HEIGHT - 6 9/16" (167 mm)
 WIDTH - 1 1/8" (28.6 mm)
 WEIGHT - 12 oz. (0.34 kg)

FEATURES:

- DESIGNED FOR SPRAYING HOT LIQUIDS AT TEMPERATURES UP TO 300° F (150°C).
- SPRAY PATTERN CAN BE ADJUSTED FROM A HOLLOW CONE PATTERN TO A SOLID STREAM, BY PULLING BACK ON TRIGGER.
- FOR PRESSURES UP TO 250 PSI (17 bar).
- OUTER HOUSING AND TRIGGER GUARD MOLDED OF TOUGH NYLON MATERIAL DESIGNED TO WITHSTAND HIGH IMPACT AND ROUGH USAGE.
- TRIGGER LOCK HOLDS TRIGGER IN "OFF" POSITION.
- VITON LIP SEAL REQUIRES NO ADJUSTMENT.
- BUNA-N BUMPER PROTECTS SPRAY TIP FROM DAMAGE.

FLOW RATES IN SOLID STREAM POSITION							
P.S.I. (bar)	20 (1.5)	40 (3)	60 (4)	80 (6)	100 (7)	150 (10)	250 (17)
GPM (l/min)	2.75 (11)	4 (16)	5 (19)	5.5 (22)	6.25 (24)	7.75 (29)	10 (38)

DESCRIPTION:
 NO. AA30-20940 GUNJET®
 SPRAY GUN WITH
 VARIABLE SPRAY PATTERN



Spraying Systems Co.®
 Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 4

Ref.

Data Sheet No.

20940

SHEET OF