



**FEATURES:**

- DESIGNED FOR USE WITH QUICK TEEJET® VARI-SPACING CLAMPS - SEE D.S. 21386-4.
- USED WITH QUICK TEEJET® CAPS
- HOSE SHANK AVAILABLE AS SINGLE, DOUBLE, OR TRIPLE IN 3/8", 1/2", AND 3/4" SIZES.
- MADE OF CORROSION RESISTANT MATERIALS.
- MAXIMUM OPERATING PRESSURE - 125 PSI (9 bar)

STYLE	BODY No.	"A" DIM. (APPROX.)	"B" DIM. (APPROX.)	"C" DIM. (APPROX.)
SINGLE	18635-111-406-NYB*	1 9/16" (40 mm)	2 1/4" (57 mm)	11/16" (17 mm)
	18638-111-540-NYB*	1 9/16" (40 mm)	2 1/4" (57 mm)	11/16" (17 mm)
	18719-111-785-NYB*	2 17/64" (51 mm)	2 1/4" (57 mm)	11/16" (17 mm)
DOUBLE	18636-112-406-NYB*	3 1/8" (79 mm)	2 1/4" (57 mm)	11/16" (17 mm)
	18639-112-540-NYB*	3 1/8" (79 mm)	2 1/4" (57 mm)	11/16" (17 mm)
	18720-112-785-NYB*	3 3/4" (95 mm)	2 1/4" (57 mm)	11/16" (17 mm)
TRIPLE	18637-113-406-NYB*	3 1/8" (79 mm)	3 13/16" (97 mm)	2 1/4" (57 mm)
	18640-113-540-NYB*	3 1/8" (79 mm)	3 13/16" (97 mm)	2 1/4" (57 mm)
	18721-113-785-NYB*	3 3/4" (95 mm)	4 1/8" (105 mm)	2 1/4" (57 mm)

\* -PP FOR POLYPROPYLENE MATERIAL

**DESCRIPTION:**  
QJ100 SERIES HOSE SHANK  
NOZZLE BODIES



**Spraying Systems Co.®**

Spray Nozzles and Accessories  
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 2

Ref.

Data Sheet No.

21386-1

SHEET OF