



FEATURES:

- DESIGNED FOR USE WITH QUICK TEEJET® VARI-SPACING CLAMPS - SEE D.S. 21386-4.
- USED WITH QUICK TEEJET® CAPS
- HOSE SHANK AVAILABLE AS SINGLE, DOUBLE, OR TRIPLE IN 3/8", 1/2", AND 3/4" SIZES.
- MADE OF CORROSION RESISTANT MATERIALS.
- DRIP FREE POSITIVE SHUT-OFF.
- MAXIMUM OPERATING PRESSURE - 125 PSI (9 bar)

STYLE	BODY No.	"A" DIM. (APPROX.)	"B" DIM. (APPROX.)	"C" DIM. (APPROX.)
SINGLE	19349-211-406-NYB	1 15/16" (49 mm)	13/16" (21 mm)	3 11/16" (94 mm)
	19349-211-540-NYB	1 15/16" (49 mm)	13/16" (21 mm)	3 11/16" (94 mm)
	19349-211-785-NYB	2 3/16" (56 mm)	13/16" (21 mm)	3 11/16" (94 mm)
DOUBLE	19350-212-406-NYB	3 1/8" (79 mm)	13/16" (21 mm)	3 11/16" (94 mm)
	19350-212-540-NYB	3 1/8" (79 mm)	13/16" (21 mm)	3 11/16" (94 mm)
	19350-212-785-NYB	3 3/4" (95 mm)	13/16" (21 mm)	3 11/16" (94 mm)
TRIPLE	19351-213-406-NYB	3 1/8" (79 mm)	2 1/8" (54 mm)	4 13/16" (122 mm)
	19351-213-540-NYB	3 1/8" (79 mm)	2 1/8" (54 mm)	4 13/16" (122 mm)
	19351-213-785-NYB	3 3/4" (95 mm)	2 9/16" (65 mm)	4 7/8" (124 mm)

DESCRIPTION:
QJ200 SERIES HOSE SHANK
DIAPHRAM CHECK VALVES



Spraying Systems Co.®

Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 4

Ref.

Data Sheet No.

21386-2

SHEET OF