



FEATURES:

- DESIGNED FOR USE WITH QUICK TEEJET VARI-SPACING CLAMP - SEE DATA SHEET 21386-4
- HOSE SHANK AVAILABLE AS A SINGLE, DOUBLE, OR TRIPLE IN 3/8", 1/2", AND 3/4" SIZES.
- MADE OF CORROSION RESISTANT MATERIALS.
- MAXIMUM OPERATING PRESSURE - 125 PSI [9 bar]
- 1/4" NPT FEMALE OUTLET.

STYLE	BODY NO.	"A" DIM. (APPROX.)	"B" DIM. (APPROX.)	"C" DIM. (APPROX.)
SINGLE	18642-NYB-406	1 15/16" (49 mm)	13/16" (21 mm)	7/8" (22 mm)
	18645-NYB-540	1 15/16" (49 mm)	13/16" (21 mm)	7/8" (22 mm)
	18724-NYB-785	2 3/16" (56 mm)	13/16" (21 mm)	7/8" (22 mm)
DOUBLE	18643-NYB-406	3 1/8" (79 mm)	13/16" (21 mm)	7/8" (22 mm)
	18646-NYB-540	3 1/8" (79 mm)	13/16" (21 mm)	7/8" (22 mm)
	18725-NYB-785	3 3/4" (95 mm)	13/16" (21 mm)	7/8" (22 mm)
TRIPLE	18644-NYB-406	3 1/8" (79 mm)	2 1/8" (54 mm)	7/8" (22 mm)
	18647-NYB-540	3 1/8" (79 mm)	2 1/8" (54 mm)	7/8" (22 mm)
	18726-NYB-785	3 3/4" (95 mm)	2 9/16" (65 mm)	7/8" (22 mm)

DESCRIPTION:
 SINGLE, DOUBLE, AND TRIPLE
 HOSE SHANK CONNECTOR
 BODIES WITH 1/4" NPT (F)
 OUTLET CONNECTION



Spraying Systems Co.®

Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1

Ref.

Data Sheet No.

21386-5

SHEET OF