



THE SKETCH ABOVE SHOWS A CONTINUOUS FLOW SYSTEM USING 2 LIQUID STRAINERS, 2 GAUGES MOUNTED ON SPLIT-EYELET CONNECTORS AND 3 #AA344M-3 BALL VALVES. ONLY ONE STRAINER IS OPERATED AT ONE TIME. WHEN THE OUTLET PRESSURE IN THE LINE GETS SUBSTANTIALLY LOWER THAN THE INLET LINE PRESSURE, THAT LINE IS CLOSED AND LIQUID FLOW IS DIVERTED TO THE OTHER LINE, THEREBY MAINTAINING A CONTINUOUS SYSTEM.

NOTE: THIS ARRANGEMENT IS NOT RECOMMENDED FOR THE PRESSURE SIDE OF POSITIVE DISPLACEMENT TYPE PUMPS.

**DESCRIPTION:**  
 CONTINUOUS FLOW SYSTEM  
 USING 2 SELF-CLEANING  
 LIQUID STRAINERS AND  
 3 AA344M-3 BALL VALVES



**Spraying Systems Co.**  
 Spray Nozzles and Accessories  
 P.O. Box 7900 - Wheaton, Ill. 60189-7900

Rev. No.

Data Sheet No.

23196-2

Ref.

SHEET OF