






PLUG VALVE TYPE	PLUG VALVE NO.	CONNECTION (INLET x OUTLET)	OVERALL LENGTH	HEIGHT
FEMALE x FEMALE 	23220-1/4F x 1/4F	1/4" NPT(F) x 1/4" NPT(F)	1-3/4" (44.5 mm)	1-5/32" (29.4 mm)
	B23220-1/4F x 1/4F	1/4" BSPT(F) x 1/4" BSPT(F)		
	23220-1/8F x 1/8F	1/8" NPT(F) x 1/8" NPT(F)		
	B23220-1/8F x 1/8F	1/8" BSPT(F) x 1/8" BSPT(F)		
MALE x 11/16"-16 	23220-1/4M x T	1/4" NPT(M) x 11/16"-16(M)	2-1/8" (54.0 mm)	1-5/32" (29.4 mm)
	B23220-1/4M x T	1/4" BSPT(M) x 11/16"-16(M)		
FEMALE x 11/16"-16 	23220-1/4F x T	1/4" NPT(F) x 11/16"-16(M)	2-1/8" (54.0 mm)	1-5/32" (29.4 mm)
	B23220-1/4F x T	1/4" BSPT(F) x 11/16"-16(M)		
MALE x FEMALE 	23220-1/4M x 1/4F	1/4" NPT(M) x 1/4" NPT(F)	1-3/4" (44.5 mm)	1-5/32" (29.4 mm)
	B23220-1/4M x 1/4F	1/4" BSPT(M) x 1/4" BSPT(F)		
FEMALE x MALE 	23220-1/4F x 1/4M	1/4" NPT(F) x 1/4" NPT(M)	1-3/4" (44.5 mm)	1-5/32" (29.4 mm)
	B23220-1/4F x 1/4M	1/4" BSPT(F) x 1/4" BSPT(M)		

LEVER SHOWN IN "ON" SPRAYING POSITION
(FLOW IN DIRECTION OF ARROW)

MATERIAL:

BRASS BODY WITH ONE PIECE CELCON_® PLUG/HANDLE COMBINATION,
BUNA-N O-RINGS, AND STAINLESS STEEL SPRING PIN AND RETAINING RING.

FEATURES:

- QUICK AND EASY "SHUT-OFF".
- "ON-OFF" ACTION BY ROTATING LEVER 90° FROM "ON" TO "OFF" POSITION OR BY USING A 1/4" HEX ALLEN WRENCH IN THE OPENING IN THE TOP OF THE LEVER.
- MAXIMUM OPERATING PRESSURE - 400 PSI (27 bar)
- 23220- x T ARE FOR USE WITH TEEJET CAPS, TIPS AND ACCESSORIES UP TO THEIR MAXIMUM RATED PRESSURES.
- LOW-PROFILE HANDLE DESIGN.

DESCRIPTION:

NO. 23220-
PLUG VALVES



Spraying Systems Co.[®]

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No.

Ref.

Data Sheet No.

23220

SHEET OF