

NOTE: 1/4" NPS(M)
INLET CONN.
(OPTIONAL)


- MAXIMUM OPERATING PRESSURE - 75 PSI (5.2 bar).
- MINIMUM PRESSURE TO CHARGE UNIT - 25 PSI (1.7 bar).
(SPECIAL SPRING AVAILABLE TO REDUCE CHARGING PRESSURE FOR LOW DOSAGE APPLICATIONS).

THE ADJUSTABLE METERING SUB-ASSEMBLY IS A PRECISION DELIVERY DEVICE WHICH DISCHARGES ACCURATE DOSAGES WITHIN A RANGE OF 1 TO 16 MILLILITERS WITH A SINGLE PULL OF THE METERJET TRIGGER. RELEASE OF THE TRIGGER AUTOMATICALLY RECHARGES THE UNIT READY FOR THE NEXT DOSAGE.

THE UNIT ACCEPTS ALL UNIJET® SPRAY TIPS FOR MANY TYPES OF APPLICATIONS.

DESCRIPTION:

**NO. 23623-31-1/4F
METERJET GUN ASSEMBLY**



Spraying Systems Co.®
 Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No.	Data Sheet No. 23623-1
Ref.	SHEET OF