



- MAXIMUM OPERATING PRESSURE - 75 PSI (5.2 bar).
- MINIMUM PRESSURE TO CHARGE UNIT - 25 PSI (1.7 bar).
(SPECIAL SPRING AVAILABLE TO REDUCE CHARGING PRESSURE FOR LOW DOSAGE APPLICATIONS).

THE ADJUSTABLE METERING SUB-ASSEMBLY IS A PRECISION DELIVERY DEVICE WHICH DISCHARGES ACCURATE DOSAGES WITHIN A RANGE OF 1 TO 16 MILLILITERS WITH A SINGLE PULL OF THE METERJET TRIGGER. RELEASE OF THE TRIGGER AUTOMATICALLY RECHARGES THE UNIT READY FOR THE NEXT DOSAGE.

THE UNIT ACCEPTS ALL UNIJET® SPRAY TIPS FOR MANY TYPES OF APPLICATIONS.

DESCRIPTION:

NO. 23624-30L-1/4 &
NO. B23624-30L-1/4
METERJET GUN ASSEMBLIES



Spraying Systems Co.®

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Ref.

Data Sheet No.

23624-1

SHEET OF