



- MAXIMUM OPERATING PRESSURE - 75 PSI (5.2 bar).
- MINIMUM PRESSURE TO CHARGE UNIT - 25 PSI (1.7 bar).
- ALSO AVAILABLE AS MODEL NO. 23624L-30L-1/4 AND MODEL NO. B23624L-30L-1/4 METERJET™ GUN ASSEMBLIES WITH A REDUCED MINIMUM CHARGING PRESSURE OF 20 PSI (1.4 bar) FOR LOW DOSAGE APPLICATIONS.

THE NO. 23624-30L-1/4 METERJET™ GUN ASSEMBLY IS USED AS A HERBICIDE SPOT GUN APPLICATOR FOR SOIL, FOLIAR, THINLINE BASAL BARK AND TREE STUMP TREATING APPLICATIONS.

THE ADJUSTABLE METERING SUB-ASSEMBLY IS A PRECISION DELIVERY DEVICE WHICH DISCHARGES ACCURATE DOSAGES WITHIN A RANGE OF 1 TO 16 MILLILITERS WITH A SINGLE PULL OF THE METERJET TRIGGER. RELEASE OF THE TRIGGER AUTOMATICALLY RECHARGES THE UNIT READY FOR THE NEXT DOSAGE.

THE UNIT ACCEPTS ALL TEEJET® SPRAY TIPS FOR MANY TYPES OF APPLICATIONS.

DESCRIPTION:

NO. 23624-30L-1/4 &
NO. B23624-30L-1/4
METERJET GUN ASSEMBLIES



Spraying Systems Co.®

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Data Sheet No.

23624

Ref.

SHEET OF