



W = Maximum Effective Coverage
with nozzle mounted at 36" height.

TeeJet 3/4" NPT OFF-CENTER SINGLE SWIVEL NOZZLE NO.	Liquid Pressure in psi	Nozzle Capacity Imp. GPM	"W" Feet	SPRAYING HEIGHT "H"=36"		
				IMPERIAL GALLONS PER ACRE		
				5 MPH	10 MPH	15 MPH
4629-3/4T-OC10	30	.72	18	4.0	2.0	1.3
	40	.83	18½	4.5	2.2	1.5
	60	1.0	18½	5.5	2.7	1.8
4629-3/4T-OC20	30	1.4	23½	6.1	3.0	2.0
	40	1.7	24½	6.7	3.4	2.2
	60	2.0	24½	8.2	4.1	2.7
4629-3/4T-OC40	30	2.9	26	11.0	5.5	3.7
	40	3.3	27	12.2	6.1	4.1
	60	4.1	27	15.0	7.5	5.0
4629-3/4T-OC80	30	5.8	29	19.7	9.8	6.6
	40	6.7	30	22	11.0	7.3
	60	8.2	30	27	13.5	9.0
4629-3/4T-OC150	30	10.8	30½	35	17.6	11.7
	40	12.5	31½	39	19.6	13.1
	60	15.3	31½	48	24	16.0
4629-3/4T-OC300	30	22	32	67	33	22
	40	25	33	75	37	25
	60	31	33½	90	45	30

TABULATION BASED ON SPRAYING WATER AT 70°F.

DESCRIPTION:

IMPERIAL GALLONS PER ACRE
USING
4629-3/4T-OC- -
TEEJET SINGLE SWIVEL SPRAY
NOZZLES WITH OFF-CENTER
FLAT SPRAY TIPS



Spraying Systems Co.[®]

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Ref.

Data Sheet No.

23853

SHEET OF