



MATERIAL - STAINLESS STEEL
WITH CELCON SLEEVE

**FULL CONE
SPRAY PATTERN**

TIP NO.	ORIFICE DIA. (NOMINAL)	CAPACITY gal/min AT PRESSURE P.S.I.					SPRAY ANGLE	
		25 P.S.I.	30 P.S.I.	40 P.S.I.	50 P.S.I.	60 P.S.I.	25 P.S.I.	40 P.S.I.
FL-5VS	.057"	.42	.46	.52	.57	.62	120°	120°
FL-6.5VS	.065"	.53	.57	.65	.72	.78	120°	120°
FL-8VS	.073"	.64	.70	.79	.87	.94	120°	120°
FL-10VS	.086"	.81	.88	1.0	1.1	1.2	120°	120°
FL-15VS	.098"	1.2	1.3	1.5	1.7	1.8	120°	120°

TYPE "FL-__VS" TIPS ARE USED WITH S.S.CO. UNIJET SPRAY NOZZLES AND GUNJET SPRAY GUNS.

DESCRIPTION:

TYPE "FL- VS" FULLCONE
SPRAY TIPS WITH
120° SPRAY ANGLE



Spraying Systems Co.[®]

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Data Sheet No.

25554

Ref.

SHEET OF