

- TANK RINSING SHOULD BE PERFORMED AT PRESSURES BETWEEN 10 P.S.I. TO 40 P.S.I. (1 - 3 bar)
- ONE RINSING NOZZLE PER SECTION OF TANK IF BAFFLES ARE PRESENT INSIDE THE TANK
- TANK SHOULD BE RINSED AND FLUSHED IN THREE REPETITIONS TO ACHIEVE EFFECTIVE RINSING



SUGGESTED TANK RINSING NOZZLES

21400-HSS18-315SS

27500E-3/4-18-TEF

3/4" N.P.T. (F) OR
3/4" B.S.P.T. (F)
INLET CONN.

3/4" N.P.T. (F)



MULTIPLE
SPRAY
ORIFICES

MATERIAL: TEFLON

MATERIAL:
TYPE 316 STAINLESS STEEL

SEE DATA SHEET #25911
FOR MORE INFORMATION

SEE DATA SHEET #25910
FOR MORE INFORMATION

DESCRIPTION:
TANK RINSING DIAGRAM FOR
AGRICULTURAL SPRAYER TANKS



Spraying Systems Co.

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Data Sheet No.

25743

Ref.

SHEET OF