


FEATURES:

- THE 27500 ROTATING TYPE NOZZLES HAVE A LIQUID DRIVEN ROTATING SPRAY HEAD WITH ORIFICES THAT PRODUCE HIGH IMPACT SOLID STREAM SPRAYS WHICH ARE PRECISELY POSITIONED TO PROVIDE EFFECTIVE INTERNAL WETTING OF TANKS.
- SIMPLE TWO-PIECE CONSTRUCTION. NO INTERNAL FLOW OBSTRUCTIONS.
- TYPE OF COVERAGE: 360° FULL COVERAGE.
- MADE OF CORROSION RESISTANT MATERIAL – TEFLON.
- SELF-LUBRICATING AND SELF-FLUSHING.

NOZZLE NO.	CAPACITY – GALLONS PER MINUTE					TYPE OF COVERAGE	SPRAY ANGLE
	10 PSI	20 PSI	30 PSI	40 PSI	50 PSI		
27500E-3/4-18-TEF	9	12.7	15.6	18	20		360°
	CAPACITY – L/min						
	0.7 bar	1.5 bar	2 bar	3 bar	3.5 bar		
	34	50	58	71	77		

DESCRIPTION:

**NO. 27500-3/4-18-TEF
LOW PRESSURE ROTATING TYPE
TANK CLEANING NOZZLE**



Spraying Systems Co.®

**Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60189-7900**

Rev. No.

Data Sheet No.

25911

Ref.

SHEET OF