


**FEATURES:**

- EXTENSION MADE OF BRASS TUBING.
- SHUT-OFF LOCATED BEHIND ORIFICE TIP TO PREVENT DRIPPING.
- SMOOTH AND EASY TO OPERATE...LIGHT TRIGGER PULL WITH POSITIVE FEEL MAINTAINED AND CONTROLLED, EVEN UNDER MAXIMUM DESIGN OPERATING FLOW AND PRESSURE CONDITIONS.
- HANDLE REMAINS COMFORTABLE DURING HOT SPRAYING OPERATING UP TO 200°F (93° C).
- HANDLE GRIP DESIGNED FOR GLOVED OR UN-GLOVED HAND.
- BUNA-N STEM SEAL.
- TEFLON VALVE SEAT.
- STAINLESS STEEL SHUT-OFF NEEDLE.
- SINGLE PIECE BRASS FORGED VALVE BODY.
- TRIGGER LOCK RETRACTS FLUSH IN HANDLE WITH DETENT HOLD.
- SHORT HAND GRIP (HANDLE TO TRIGGER).
- PRESSURES UP TO 250 PSI (17.2 Bar).
- FLOW RATES UP TO 5 GPM (19 L/Min.).
- MAXIMUM TEMPERATURE - 200° F (93° C).
- OUTER HOUSING WITH TRIGGER GUARD MOLDED OF HIGH IMPACT NYLON MATERIAL.
- WILL ACCOMMODATE STANDARD SS CO. ACCESSORIES FOR THE INLET CONNECTION (WITHIN THE ACCESSORIES' PRESSURE LIMITATIONS) SUCH AS: SWIVELS, STRAINERS AND ADAPTERS.

GUNJET NO.	EXTENSION NO.	EXTENSION LENGTH		NET WEIGHT	
		INCHES	mm	OZ.	kg
30L-22425-8	22426-8	8"	203 mm	16 oz.	0.45 kg
30L-22425-18	22426-18	18"	457 mm	19 oz.	0.54 kg
30L-22425-24	22426-24	24"	610 mm	20 oz.	0.57 kg
30L-22425-36	22426-36	36"	914 mm	23 oz.	0.65 kg
30L-22425-48	22426-48	48"	1219 mm	25 oz.	0.71 kg

DESCRIPTION: NO. 30L-22425-- GUNJET SPRAY GUN WITH NO. 22426-EXTENSION		 <b>Spraying Systems Co.®</b> Spray Nozzles and Accessories P.O. Box 7900 - Wheaton, Il. 60189-7900
Rev. No.	Data Sheet No.	
Ref.	<b>30L-22425</b>	SHEET OF