



LENGTH - 5 11/16" (144 mm)  
 HEIGHT - 3 1/4" (83 mm)  
 WEIGHT - 13.5 oz. (0.34 kg)

**FEATURES:**

- SPRAY PATTERN CAN BE ADJUSTED FROM A HOLLOW CONE PATTERN TO A SOLID STREAM BY TRIGGER CONTROL.
- POSITIVE TRIGGER ACTION PROVIDES DRIP FREE SHUT-OFF.
- BRASS CONSTRUCTION WITH STAINLESS STEEL TRIGGER & BUNA-N BUMPER. INTERNAL PACKING AND VALVE SEAT RING ARE MADE OF TEFLON.
- FOR PRESSURES UP TO 500 PSI (34 bar).

FLOW RATES IN SOLID STREAM POSITION							
P.S.I. (bar)	20 (1.5)	40 (3)	60 (4)	100 (7)	200 (14)	300 (20)	500 (34)
GPM (l/min)	2.2 (9.0)	3.2 (12.8)	4.0 (14.8)	5.1 (19.8)	7.5 (28.2)	9.3 (33.9)	11.7 (44.5)

**DESCRIPTION:**

NO. AA31-39430 GUNJET®  
 SPRAY GUN WITH  
 VARIABLE SPRAY PATTERN



**Spraying Systems Co.®**

Spray Nozzles and Accessories  
 P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Data Sheet No.

**31-39430**

Ref.

SHEET OF