



NOZZLE NO.		MESH OF SCREEN	CAPACITY G.P.M. (Gallons Per Minute) AND SPRAY ANGLE AT p.s.i. (lbs per square inch)									
TYPE T FEMALE CONN.	TYPE TT MALE CONN.		20	25	30	40	60	80	100	150	200	300
1/4 T 150 015	1/4 TT 150 015	100			.13 143°	.15 150°	.18 154°	.21 156°	.24 158°	.29 160°	.34 162°	.41 163°
1/4 T 150 02	1/4 TT 150 02	100			.17 144°	.20 150°	.24 154°	.28 156°	.31 158°	.39 160°	.45 162°	.55 163°
1/4 T 150 03	1/4 TT 150 03	100			.26 144°	.30 150°	.37 154°	.42 157°	.47 159°	.58 161°	.67 163°	.82 164°
1/4 T 150 04	1/4 TT 150 04	50			.35 145°	.40 150°	.48 155°	.57 157°	.63 159°	.77 161°	.89 163°	1.10 164°
1/4 T 150 06	1/4 TT 150 06	50	.47 143°	.52 146°	.60 150°	.73 155°	.85 158°	.95 160°	1.16 162°	1.34 164°	1.64 164°	
1/4 T 150 08	1/4 TT 150 08	50	.63 144°	.69 147°	.80 150°	.98 155°	1.13 158°	1.26 160°	1.55 162°	1.79 164°	2.20 164°	
1/4 T 150 09	1/4 TT 150 09	50	.71 144°	.78 147°	.90 150°	1.10 155°	1.27 158°	1.42 160°	1.74 162°	2.01 164°	2.46 164°	

TABULATION IS BASED ON WATER AT TEMPERATURE OF 70° F.

NOTE: TO ORDER DOUBLE OUTLET TEEJET TIPS ONLY... SPECIFY NO. TQ150---  
(EXAMPLE: NO. TQ150015)

**DESCRIPTION:**

1/4 T 150-- & 1/4 TT 150--  
DOUBLE OUTLET  
TEEJET NOZZLES



**Spraying Systems Co.®**

Spray Nozzles and Accessories  
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Data Sheet No.

**3421**

Ref. 1

SHEET OF