



**FEATURES:**

- CLEAR BOWL FOR EASY VISUAL INSPECTION OF SCREEN
- POLYPROPYLENE HEAD AND CLEAR NYLON BOWL
- BOWL EASILY REMOVED BY HAND TO CLEAN SCREEN

**MAXIMUM RECOMMENDED PRESSURE:** 150 PSI (10 bar) @ 100° F (38°C) MAX.

SCREENS			NET WEIGHT	APPROX. FLOW RATE WITH 5 PSI (0.35 bar) PRESSURE DROP
MESH SIZE	OPENING	FULL AREA		
16	.045" (1.1 mm)	7.7 SQ. IN. (49.7 cm <sup>2</sup> )	6 oz. (0.17 kg)	12 GPM (45 l/min.)
30	.021" (0.53 mm)			
50	.011" (0.28 mm)			
80	.007" (0.18 mm)			
100	.006" (0.15 mm)			

**DESCRIPTION:**  
**NO. 36234-122-1/2-NYC**  
**LIQUID STRAINER**



**Spraying Systems Co.<sup>®</sup>**  
 Spray Nozzles and Accessories  
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1

Ref.

Data Sheet No.

**36234**

SHEET OF