



FEATURES

- LONGER WEAR LIFE
- RESISTS CORROSION
- ACCEPTS MORE ABRASIVE PESTICIDE FORMULATIONS
- POLYPROPYLENE BODY & CERAMIC INSERT
- POPULAR NOZZLE SIZES FIT MOST SPRAYERS
- OPERATES AT HIGHER PRESSURES UP TO 300 P.S.I. (20 bar)
- CAN BE USED WITH ALL TYPES OF TEEJET® NOZZLE BODIES

CONEJET TIP NO.	TIP COLOR (VISIFLO)	ORIFICE DIA.	MESH OF SCREEN	CAPACITY IN GPM (GALLONS PER MINUTE) AT PRESSURE PSI (LBS. PER SQ. INCH)										SPRAY ANGLE AT PSI			
				30	40	50	60	80	100	125	150	200	300	30	40	100	300
TXVK-3	YELLOW	.034"	100	.043	.050	.055	.060	.068	.075	.082	.088	.10	.12	68°	72°	80°	83°
TXVK-4	GREEN	.041"	50	.058	.067	.074	.080	.091	.10	.11	.12	.14	.17	70°	73°	80°	81°
TXVK-6	RED	.047"	50	.088	.10	.11	.12	.14	.15	.17	.18	.21	.25	71°	74°	80°	80°
TXVK-8	GRAY	.052"	50	.12	.13	.15	.16	.19	.21	.23	.25	.29	.35	71°	74°	80°	80°
TXVK-10	BLACK	.060"	50	.14	.17	.19	.20	.23	.26	.29	.31	.36	.44	72°	75°	80°	79°
TXVK-12	BROWN	.067"	50	.17	.20	.22	.24	.28	.31	.34	.38	.43	.52	73°	76°	80°	78°
TXVK-18	ORANGE	.079"	50	.26	.30	.34	.37	.42	.47	.53	.58	.67	.81	75°	77°	80°	77°
TXVK-26	LIGHT BLUE	.094"	50	.31	.43	.48	.53	.61	.68	.76	.83	.96	1.2	76°	78°	80°	76°

DESCRIPTION:
 TYPE TXVK--CERAMIC
 VISIFLO® CONEJET® TIPS



Spraying Systems Co.®

Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No.

Data Sheet No.

36393

Ref.

SHEET OF