

DG95015EVS DRIFT GUARD EVEN VISIFLO® S.S. FLAT SPRAY TIP

PRESSURE PSI	Dv0.1	Dv0.5	Dv0.9
10	259	456	652
20	193	365	558
30	150	320	481
40	134	292	437
50	126	271	410
60	122	256	391
70	119	244	378
80	118	233	369
90	117	225	363
100	116	217	359

DG9502EVS DRIFT GUARD EVEN VISIFLO® S.S. FLAT SPRAY TIP

PRESSURE PSI	Dv0.1	Dv0.5	Dv0.9
10	290	482	672
20	238	421	632
30	191	373	585
40	168	336	540
50	153	306	500
60	143	283	465
70	135	266	434
80	129	253	407
90	125	245	384
100	121	240	369

DG9503EVS DRIFT GUARD EVEN VISIFLO® S.S. FLAT SPRAY TIP

PRESSURE PSI	Dv0.1	Dv0.5	Dv0.9
10	311	500	682
20	247	444	645
30	201	393	603
40	175	354	561
50	158	326	523
60	147	303	490
70	141	284	460
80	134	269	434
90	132	257	410
100	131	248	389

DG9504EVS DRIFT GUARD EVEN VISIFLO® S.S. FLAT SPRAY TIP

PRESSURE PSI	Dv0.1	Dv0.5	Dv0.9
10	343	529	700
20	273	468	663
30	224	419	628
40	193	380	595
50	174	348	564
60	160	323	534
70	151	303	506
80	145	288	479
90	142	277	454
100	141	269	430

DG9505EVS DRIFT GUARD EVEN VISIFLO® S.S. FLAT SPRAY TIP

PRESSURE PSI	Dv0.1	Dv0.5	Dv0.9
10	361	557	722
20	287	493	684
30	235	441	648
40	204	400	613
50	183	366	581
60	169	340	551
70	159	320	522
80	153	303	494
90	150	292	468
100	148	284	443

Data is based on spraying water under laboratory conditions using Aerometrics Phase Doppler Particle Analyzer (PDPA). All values are computed utilizing the procedures for determining spray characteristics as outlined by ASTM (Standard E799)

DESCRIPTION:
 95° DRIFT GUARD EVEN VISIFLO® STAINLESS STEEL FLAT SPRAY TIPS DROP SIZE DATA IN MICROMETERS VERSUS PRESSURE

CAPACITIES DG95015EVS THRU DG9505EVS SPRAYING WATER AT 70° F



Spraying Systems Co.®

Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Ref.

Data Sheet No.

37043-13

SHEET OF