



FEATURES:

- LONGER WEAR LIFE
- RESISTS CORROSION
- ACCEPTS MORE ABRASIVE PESTICIDE FORMULATIONS
- POLYPROPYLENE BODY & CERAMIC INSERT
- POPULAR NOZZLE SIZES FIT MOST SPRAYERS
- OPERATES AT HIGHER PRESSURES UP TO 300 PSI (20 bar)
- INCORPORATES ISO COLOR CODING SCHEME

CONEJET TIP No.		TIP COLOR (VISIFLO)	ORIFICE DIA.	MESH OF SCREEN	CAPACITY IN GPM (GALLONS PER MINUTE) AT PRESSURE PSI (LBS. PER SQ. INCH)										SPRAY ANGLE AT PSI			
TYPE TXA	TYPE TXB				30	40	50	60	80	100	125	150	200	300	30	40	100	300
TXA800050VK	TXB800050VK	PURPLE	.034"	100	.043	.050	.055	.060	.068	.075	.082	.088	.10	.12	68°	72°	80°	83°
TXA800067VK	TXB800067VK	OLIVE GREEN	.041"	50	.058	.067	.074	.080	.091	.10	.11	.12	.14	.17	70°	73°	80°	81°
TXA8001VK	TXB8001VK	ORANGE	.047"	50	.088	.10	.11	.12	.14	.15	.17	.18	.21	.25	71°	74°	80°	80°
TXA80015VK	TXB80015VK	GREEN	.057"	50	.13	.15	.17	.18	.21	.23	.26	.28	.32	.39	72°	75°	80°	80°
TXA8002VK	TXB8002VK	YELLOW	.067"	50	.17	.20	.22	.24	.28	.31	.34	.38	.43	.52	73°	76°	80°	78°
TXA8003VK	TXB8003VK	BLUE	.079"	50	.26	.30	.34	.37	.42	.47	.53	.58	.67	.81	75°	77°	80°	77°
TXA8004VK	TXB8004VK	RED	.089"	50	.35	.40	.45	.49	.56	.63	.70	.77	.89	1.09	76°	78°	80°	80°

DESCRIPTION:
TYPE TXA & TXB- -VK CERAMIC VISIFLO CONEJET TIPS



Spraying Systems Co.®

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No.

Data Sheet No.

38010

Ref.

SHEET OF