


Liquid Orifice Number	Air Pressure (psi)	Approx. Air Flow (SCFM)	Liquid Pressure (psi)	Liquid Flow (GPM)	Application Rate in GPA on 20 inch Nozzle Spacing					Drop Size Category
					4 mph	5 mph	6 mph	8 mph	10 mph	
42	5.0	0.88	10.0	0.11	8.2	6.5	5.4	4.1	3.3	VC
		0.63	14.5	0.15	11.1	8.9	7.4	5.6	4.5	VC
		0.41	21.8	0.19	14.1	11.3	9.4	7.1	5.6	VC
		0.27	29.0	0.23	17.1	13.7	11.4	8.5	6.8	XC
		0.17	36.3	0.26	19.3	15.4	12.9	9.7	7.7	XC
		0.11	43.5	0.29	22	17.2	14.4	10.8	8.6	XC
		0.07	50.8	0.31	23	18.4	15.3	11.5	9.2	XC
		0.05	58.0	0.33	25	19.6	16.3	12.3	9.8	XC
		0.02	65.3	0.36	27	21	17.8	13.4	10.7	XC
	0.01	72.5	0.38	28	23	18.8	14.1	11.3	XC	
	7.3	1.28	10.0	0.093	6.9	5.5	4.6	3.5	2.8	F
		1.03	14.5	0.13	9.7	7.7	6.4	4.8	3.9	M
		0.70	21.8	0.18	13.4	10.7	8.9	6.7	5.3	C
		0.53	29.0	0.22	16.3	13.1	10.9	8.2	6.5	VC
		0.39	36.3	0.25	18.6	14.9	12.4	9.3	7.4	VC
		0.30	43.5	0.27	20	16.0	13.4	10.0	8.0	XC
		0.23	50.8	0.30	22	17.8	14.9	11.1	8.9	XC
		0.17	58.0	0.32	24	19.0	15.8	11.9	9.5	XC
		0.13	65.3	0.35	26	21	17.3	13.0	10.4	XC
		0.10	72.5	0.37	27	22	18.3	13.7	11.0	XC
		0.08	79.8	0.39	29	23	19.3	14.5	11.6	XC
		0.05	87.0	0.41	30	24	20	15.2	12.2	XC
	10.8	1.93	10.0	0.065	4.8	3.9	3.2	2.4	1.9	VF
		1.59	14.5	0.11	8.2	6.5	5.4	4.1	3.3	F
		1.26	21.8	0.15	11.1	8.9	7.4	5.6	4.5	M
		0.95	29.0	0.20	14.9	11.9	9.9	7.4	5.9	M
		0.77	36.3	0.23	17.1	13.7	11.4	8.5	6.8	C
		0.63	43.5	0.26	19.3	15.4	12.9	9.7	7.7	VC
		0.53	50.8	0.29	22	17.2	14.4	10.8	8.6	VC
		0.45	58.0	0.31	23	18.4	15.3	11.5	9.2	VC
		0.38	65.3	0.33	25	19.6	16.3	12.3	9.8	XC
		0.33	72.5	0.36	27	21	17.8	13.4	10.7	XC
		0.27	79.8	0.38	28	23	18.8	14.1	11.3	XC
		0.23	87.0	0.40	30	24	19.8	14.9	11.9	XC
	14.5	2.60	10.0	0.037	2.7	2.2	1.8	1.4	1.1	VF
		2.16	14.5	0.080	5.9	4.8	4.0	3.0	2.4	VF
		1.72	21.8	0.13	9.7	7.7	6.4	4.8	3.9	F
		1.43	29.0	0.18	13.4	10.7	8.9	6.7	5.3	M
		1.15	36.3	0.21	15.6	12.5	10.4	7.8	6.2	M
		0.97	43.5	0.25	18.6	14.9	12.4	9.3	7.4	C
		0.83	50.8	0.28	21	16.6	13.9	10.4	8.3	C
		0.72	58.0	0.30	22	17.8	14.9	11.1	8.9	VC
0.64		65.3	0.32	24	19.0	15.8	11.9	9.5	XC	
0.56		72.5	0.35	26	21	17.3	13.0	10.4	XC	
0.50		79.8	0.37	27	22	18.3	13.7	11.0	XC	
0.44		87.0	0.39	29	23	19.3	14.5	11.6	XC	

Liquid Orifice Number	Air Pressure (psi)	Approx. Air Flow (SCFM)	Liquid Pressure (psi)	Liquid Flow (GPM)	Application Rate in GPA on 20 inch Nozzle Spacing					Drop Size Category
					4 mph	5 mph	6 mph	8 mph	10 mph	
42	18.1	2.78	14.5	0.054	4.0	3.2	2.7	2.0	1.6	VF
		2.21	21.8	0.11	8.2	6.5	5.4	4.1	3.3	VF
		1.87	29.0	0.16	11.9	9.5	7.9	5.9	4.8	VF
		1.59	36.3	0.20	14.9	11.9	9.9	7.4	5.9	F
		1.31	43.5	0.23	17.1	13.7	11.4	8.5	6.8	F
		1.14	50.8	0.26	19.3	15.4	12.9	9.7	7.7	M
		1.00	58.0	0.29	22	17.2	14.4	10.8	8.6	C
		0.89	65.3	0.31	23	18.4	15.3	11.5	9.2	VC
		0.79	72.5	0.34	25	20	16.8	12.6	10.1	VC
		0.71	79.8	0.36	27	21	17.8	13.4	10.7	XC
		0.64	87.0	0.38	28	23	18.8	14.1	11.3	XC
		3.47	14.5	0.033	2.5	2.0	1.6	1.2	1.0	VF
	21.8	2.75	21.8	0.093	6.9	5.5	4.6	3.5	2.8	VF
		2.33	29.0	0.14	10.4	8.3	6.9	5.2	4.2	VF
		2.01	36.3	0.18	13.4	10.7	8.9	6.7	5.3	VF
		1.76	43.5	0.22	16.3	13.1	10.9	8.2	6.5	F
		1.48	50.8	0.25	18.6	14.9	12.4	9.3	7.4	F
		1.31	58.0	0.28	21	16.6	13.9	10.4	8.3	M
	25.4	3.35	21.8	0.069	5.1	4.1	3.4	2.6	2.0	VF
		2.81	29.0	0.12	8.9	7.1	5.9	4.5	3.6	VF
		2.45	36.3	0.16	11.9	9.5	7.9	5.9	4.8	VF
		2.18	43.5	0.20	14.9	11.9	9.9	7.4	5.9	VF
		1.91	50.8	0.23	17.1	13.7	11.4	8.5	6.8	VF
		1.65	58.0	0.26	19.3	15.4	12.9	9.7	7.7	F
	29.0	3.97	21.8	0.048	3.6	2.9	2.4	1.8	1.4	VF
		3.33	29.0	0.10	7.4	5.9	5.0	3.7	3.0	VF
		2.89	36.3	0.15	11.1	8.9	7.4	5.6	4.5	VF
		2.58	43.5	0.19	14.1	11.3	9.4	7.1	5.6	VF
		2.32	50.8	0.22	16.3	13.1	10.9	8.2	6.5	VF
		2.03	58.0	0.25	18.6	14.9	12.4	9.3	7.4	VF



49880A AIRJET ASSEMBLY

DESCRIPTION:

49880A  
AIRJET® NOZZLE  
APPLICATION RATES AND  
DROPLET SIZE CATEGORY  
INFORMATION



**Spraying Systems Co.**®

Spray Nozzles and Accessories  
P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1

Ref.

Data Sheet No.

49880-3

SHEET OF