

MODEL SPECIFICATION FOR: 356 & 490	
PART CODE	DESCRIPTION
356	356 BALL VALVE
49_	490 MANIFOLD

MANIFOLD SIZE FOR: 490	
PART CODE	DESCRIPTION
1	1 VALVE MANIFOLD
2	2 VALVE MANIFOLD
3	3 VALVE MANIFOLD
4	4 VALVE MANIFOLD
5	5 VALVE MANIFOLD

MOTOR SPECIFICATION FOR: 356 & 490	
NOTE: "E" MOTORS REQUIRE DOUBLE-POLE DOUBLE-THROW (DPDT) SWITCH.	
PART CODE	DESCRIPTION
E	SHUT-OFF VALVE
EC	SHUT-OFF VALVE

SAMPLE VALVE/MANIFOLD PART NUMBER:

356BEC — CN15AB

WIRING CONNECTOR FOR: 356 & 490	
SPECIFIES ELECTRICAL CONNECTOR STYLE AND PIN OUTS. IF NO CONNECTOR IS NEEDED LEAVE BLANK. SEE DATA SHEET 50515 FOR CODES.	

MOTOR WIRING FOR: 356 & 490	
PART CODE	DESCRIPTION
C	POSITIVELY SWITCHED w/ 0.5-METER CABLE
CN	NEGATIVELY SWITCHED w/ 0.5-METER CABLE
* C03	POSITIVELY SWITCHED w/ 0.3-METER CABLE
* CN03	NEGATIVELY SWITCHED w/ 0.3-METER CABLE
* C15	POSITIVELY SWITCHED w/ 1.5-METER CABLE
* CN15	NEGATIVELY SWITCHED w/ 1.5-METER CABLE
* C60	POSITIVELY SWITCHED w/ 6.0-METER CABLE
* CN60	NEGATIVELY SWITCHED w/ 6.0-METER CABLE
D	POSITIVELY SWITCHED w/ DIN CONNECTOR
DN	NEGATIVELY SWITCHED w/ DIN CONNECTOR

MOTOR SPEED FOR: 356 & 490	
PART CODE	DESCRIPTION
BLANK	25 RPM MOTOR 0.6-SECOND CYCLE TIME


NOTE:

490 manifolds are equipped with stainless steel clamps. Inlet fittings, outlet fittings, additional clamps and DIN cables must be ordered separately. Items marked with "*" are non-stock items. Please contact your regional sales office for ordering and availability information.

FOR MORE INFORMATION:

Please refer to the following Data Sheets:
356BEC, 490BEC, 50515, FLANGE-1 and FLANGE-2.

DESCRIPTION:
**ORDERING INFORMATION
 FOR 356 ELECTRIC SHUT-OFF
 BALL VALVES AND
 490 ELECTRIC SHUTOFF
 BALL VALVE MANIFOLDS**



Spraying Systems Co.[®]
 Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 4	DATA SHEET 56604 SHEET OF
Ref.	