

THREAD TYPE	
PART CODE	DESCRIPTION
(BLANK)	ALL THREADS TO BE NPT (IF EQUIPPED)
B	ALL THREADS TO BE BSPT (IF EQUIPPED)

MANIFOLD SIZE	
PART CODE	DESCRIPTION
0	1 BARE VALVE (NO INLETS)
1	1 VALVE MANIFOLD
2	2 VALVE MANIFOLD
3	3 VALVE MANIFOLD
4	4 VALVE MANIFOLD
5	5 VALVE MANIFOLD

MOTOR TYPE	
NOTE: "E" MOTORS REQUIRE DOUBLE-POLE DOUBLE-THROW (DPDT) SWITCH.	
PART CODE	DESCRIPTION
E	SHUT-OFF VALVE
EC	SHUT-OFF VALVE

OUTLET FITTINGS	
PART CODE	DESCRIPTION
3	3/4" PIPE THREAD
4	1" PIPE THREAD
Q	QUICK CONNECT
F	50-SERIES FLANGE

BALL MATERIAL	
PART CODE	DESCRIPTION
(BLANK)	POLYPROPYLENE BALL
S	STAINLESS STEEL BALL

LEFT SIDE/RIGHT SIDE INLET FITTINGS	
PART CODE	DESCRIPTION
4T	1" PIPE THREAD
4H	1" HOSE BARB
5H	1-1/4" HOSE BARB
B	INLET BLANK
1T	1/4" THREAD GAUGE PORT

NOTE: RIGHT AND LEFT SIDES ARE AS SEEN WITH OUTLETS FACING TOWARDS YOU.

WIRING CONNECTOR	
SPECIFIES ELECTRICAL CONNECTOR STYLE AND PIN OUTS. IF NO CONNECTOR IS NEEDED LEAVE BLANK. SEE DATA SHEET 50515 FOR CODES.	

MOTOR WIRING	
PART CODE	DESCRIPTION
C	POSITIVELY SWITCHED w/ 0.5-METER CABLE
CN	NEGATIVELY SWITCHED w/ 0.5-METER CABLE
* C03	POSITIVELY SWITCHED w/ 0.3-METER CABLE
* CN03	NEGATIVELY SWITCHED w/ 0.3-METER CABLE
* C15	POSITIVELY SWITCHED w/ 1.5-METER CABLE
* CN15	NEGATIVELY SWITCHED w/ 1.5-METER CABLE
* C60	POSITIVELY SWITCHED w/ 6.0-METER CABLE
* CN60	NEGATIVELY SWITCHED w/ 6.0-METER CABLE
D	POSITIVELY SWITCHED w/ DIN CONNECTOR
DN	NEGATIVELY SWITCHED w/ DIN CONNECTOR

SAMPLE VALVE/MANIFOLD PART NUMBER:
B441BEC-4S4H4T-CN15AB

NOTE:
 Outlet fittings and DIN cables must be ordered separately. Items marked with "*" are non-stock items. Please contact your regional sales office for ordering information.

FOR MORE INFORMATION:
 Please refer to the following Data Sheets: 440BEC, 50515, FLANGE-1 and FLANGE-2.

DESCRIPTION:
ORDERING INFORMATION FOR 440B ELECTRIC SHUT-OFF BALL VALVE MANIFOLD



Spraying Systems Co.
 Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, IL 60189-7900

Rev. No. 1
 Ref.

DATA SHEET
56606
 SHEET OF