



THE DIAPHRAGM TEEJET NOZZLE WITH #5927 SHUT-OFF ASSEMBLY PROVIDES EFFICIENT CHECK VALVE OPERATION TOGETHER WITH A QUICK EASY MEANS OF SHUTTING OFF THE SPRAY COMPLETELY WITHOUT DISTURBING THE OPERATION OF OTHER NOZZLES ON THE BOOM OR MANIFOLD. A WING NUT IS USED TO LOCK THE SHUT-OFF SCREW IN THE "OPEN" OR "SHUTOFF" POSITION, SO THAT THESE SETTINGS CANNOT BE CHANGED BY VIBRATION OR SHOCK.

INSTRUCTIONS

- TO "OPEN" NOZZLE FOR SPRAYING: LOOSEN WING NUT; BACK-OFF SHUT OFF SCREW UNTIL IT STOPS; LOCK WITH WING NUT.
- TO "SHUT-OFF" NOZZLE FLOW: LOOSEN WING NUT; SCREW DOWN THE SHUT-OFF SCREW BY HAND UNTIL IT SEATS; LOCK WITH WING NUT.

FOR DETAILS ON DIAPHRAGM CHECK VALVE SEE DATA SHEET #466AA.

DESCRIPTION:
DIAPHRAGM TEEJET NOZZLE
WITH
NO. 5927 SHUT-OFF ASSEMBLY



Spraying Systems Co.®

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Data Sheet No.

6033

Ref.

SHEET OF