



THE #6135 -- DIAPHRAGM TEEJET IS RECOMMENDED FOR FLOW RATES FROM 1 G.P.M. TO 8 G.P.M.. FOR FLOW RATES LESS THAN 1 G.P.M. THE $\frac{1}{8}$ " DIAPHRAGM TEEJET AS SHOWN ON DATA SHEET No. 4664 IS RECOMMENDED.

DIAPHRAGM ASSEMBLY CAN BE TAKEN APART BY HAND... SPRING CLIP LOCKS RETAINER IN PLACE... DIAPHRAGM IS MADE OF SPECIAL RESISTANT SYNTHETIC RUBBER WHICH IS NOT AFFECTED BY MOST LIQUIDS... EASILY REPLACED.

CAN BE SUPPLIED WITH ANY FLAT SPRAY TIP (SEE DATA SHEET 2851), OR FULL CONE SPRAY TIP (SEE DATA SHEET 4517).

FLOW RATE	PRESSURE DROP THROUGH NOZZLE	
	NO. 6135- $\frac{1}{4}$	NO. 6135- $\frac{3}{8}$
1 G.P.M.	$\frac{1}{4}$ p.s.i.	$\frac{1}{4}$ p.s.i.
2 " "	1 " "	$\frac{3}{8}$ " "
3 " "	$2\frac{1}{4}$ " "	1 " "
4 " "	4 " "	$2\frac{1}{4}$ " "
5 " "	6 " "	4 " "
6 " "	$8\frac{1}{2}$ " "	6 " "
7 " "	12 " "	9 " "
8 " "	$15\frac{1}{2}$ " "	11 " "

DESCRIPTION:

NO. 6135-1/4 AND NO. 6135-3/8
DIAPHRAGM TEEJET NOZZLE



Spraying Systems Co.[®]

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Data Sheet No.

6135

Ref.

SHEET OF