

CONEJET TIP NO.	LIQUID PRESSURE IN P.S.I.	CAPACITY 1-NOZZLE IN G.P.H.	1 NOZZLE PER 40'							
			GALLONS PER ACRE							
			3	4	5	6	7	8	8	
TX 1 (100 MESH)	30	1.0	.78	.85	.92	.97	1.01	1.05	1.09	
	40	1.0	.85	.92	.97	1.01	1.05	1.09	1.13	
	50	1.1	.91	.98	1.03	1.07	1.11	1.15	1.19	
	60	1.1	.98	1.05	1.10	1.14	1.18	1.22	1.26	
TX 2 (100 MESH)	30	1.1	1.1	1.2	1.3	1.4	1.5	1.6	1.7	
	40	1.2	1.2	1.3	1.4	1.5	1.6	1.7	1.8	
	50	1.3	1.3	1.4	1.5	1.6	1.7	1.8	1.9	
	60	1.4	1.4	1.5	1.6	1.7	1.8	1.9	2.0	
TX 3 (100 MESH)	30	1.2	1.2	1.3	1.4	1.5	1.6	1.7	1.8	
	40	1.3	1.3	1.4	1.5	1.6	1.7	1.8	1.9	
	50	1.4	1.4	1.5	1.6	1.7	1.8	1.9	2.0	
	60	1.5	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
TX 4 (50 MESH)	30	1.3	1.3	1.4	1.5	1.6	1.7	1.8	1.9	
	40	1.4	1.4	1.5	1.6	1.7	1.8	1.9	2.0	
	50	1.5	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
	60	1.6	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
TX 5 (50 MESH)	30	1.4	1.4	1.5	1.6	1.7	1.8	1.9	2.0	
	40	1.5	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
	50	1.6	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
	60	1.7	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
TX 8 (50 MESH)	30	1.5	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
	40	1.6	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
	50	1.7	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
	60	1.8	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
TX 10 (50 MESH)	30	1.6	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
	40	1.7	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
	50	1.8	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
	60	1.9	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
TX 12 (50 MESH)	30	1.7	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
	40	1.8	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
	50	1.9	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
	60	2.0	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
TX 14 (50 MESH)	30	1.8	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
	40	1.9	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
	50	2.0	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
	60	2.1	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
TX 18 (50 MESH)	30	1.9	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
	40	2.0	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
	50	2.1	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
	60	2.2	2.2	2.3	2.4	2.5	2.6	2.7	2.8	
TX 26 (50 MESH)	30	2.0	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
	40	2.1	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
	50	2.2	2.2	2.3	2.4	2.5	2.6	2.7	2.8	
	60	2.3	2.3	2.4	2.5	2.6	2.7	2.8	2.9	

CONEJET TIP NO.	LIQUID PRESSURE IN P.S.I.	CAPACITY 2-NOZZLES IN G.P.H.	2 NOZZLES PER 40'							
			GALLONS PER ACRE							
			3	4	5	6	7	8	8	
TX 1 (100 MESH)	30	1.8	1.1	1.2	1.3	1.4	1.5	1.6	1.7	
	40	1.9	1.2	1.3	1.4	1.5	1.6	1.7	1.8	
	50	2.0	1.3	1.4	1.5	1.6	1.7	1.8	1.9	
	60	2.1	1.4	1.5	1.6	1.7	1.8	1.9	2.0	
TX 2 (100 MESH)	30	2.0	1.2	1.3	1.4	1.5	1.6	1.7	1.8	
	40	2.1	1.3	1.4	1.5	1.6	1.7	1.8	1.9	
	50	2.2	1.4	1.5	1.6	1.7	1.8	1.9	2.0	
	60	2.3	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
TX 3 (100 MESH)	30	2.1	1.3	1.4	1.5	1.6	1.7	1.8	1.9	
	40	2.2	1.4	1.5	1.6	1.7	1.8	1.9	2.0	
	50	2.3	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
	60	2.4	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
TX 4 (50 MESH)	30	2.2	1.4	1.5	1.6	1.7	1.8	1.9	2.0	
	40	2.3	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
	50	2.4	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
	60	2.5	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
TX 6 (50 MESH)	30	2.3	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
	40	2.4	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
	50	2.5	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
	60	2.6	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
TX 8 (50 MESH)	30	2.4	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
	40	2.5	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
	50	2.6	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
	60	2.7	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
TX 10 (50 MESH)	30	2.5	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
	40	2.6	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
	50	2.7	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
	60	2.8	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
TX 12 (50 MESH)	30	2.6	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
	40	2.7	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
	50	2.8	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
	60	2.9	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
TX 14 (50 MESH)	30	2.7	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
	40	2.8	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
	50	2.9	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
	60	3.0	2.2	2.3	2.4	2.5	2.6	2.7	2.8	
TX 18 (50 MESH)	30	2.8	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
	40	2.9	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
	50	3.0	2.2	2.3	2.4	2.5	2.6	2.7	2.8	
	60	3.1	2.3	2.4	2.5	2.6	2.7	2.8	2.9	
TX 26 (50 MESH)	30	2.9	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
	40	3.0	2.2	2.3	2.4	2.5	2.6	2.7	2.8	
	50	3.1	2.3	2.4	2.5	2.6	2.7	2.8	2.9	
	60	3.2	2.4	2.5	2.6	2.7	2.8	2.9	3.0	

CONEJET TIP NO.	LIQUID PRESSURE IN P.S.I.	CAPACITY 3-NOZZLES IN G.P.H.	3 NOZZLES PER 40'							
			GALLONS PER ACRE							
			3	4	5	6	7	8	8	
TX 1 (100 MESH)	30	2.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	
	40	2.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	
	50	2.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
	60	2.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
TX 2 (100 MESH)	30	2.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	
	40	2.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
	50	2.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
	60	2.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
TX 3 (100 MESH)	30	2.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	
	40	2.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
	50	2.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
	60	2.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
TX 4 (50 MESH)	30	2.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	
	40	2.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
	50	2.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
	60	2.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
TX 6 (50 MESH)	30	2.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	
	40	2.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
	50	2.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
	60	2.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
TX 8 (50 MESH)	30	2.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	
	40	2.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
	50	2.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
	60	3.0	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
TX 10 (50 MESH)	30	2.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5	
	40	2.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
	50	3.0	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
	60	3.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	
TX 12 (50 MESH)	30	2.9	2.0	2.1	2.2	2.3	2.4	2.5	2.6	
	40	3.0	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
	50	3.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	
	60	3.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	
TX 14 (50 MESH)	30	3.0	2.1	2.2	2.3	2.4	2.5	2.6	2.7	
	40	3.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	
	50	3.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	
	60	3.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	
TX 18 (50 MESH)	30	3.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	
	40	3.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	
	50	3.3	2.4	2.5	2.6	2.7	2.8	2.9	3.0	
	60	3.4	2.5	2.6	2.7	2.8	2.9	3.0	3.1	
TX 26 (50 MESH)	30	3.2	2.3	2.4						