


THE 8060 SUCTION STRAINER IS A LARGE CAPACITY UNIT THAT IS QUICKLY ATTACHED TO INTAKE HOSE BY MEANS OF A HOSE SHANK CONNECTION... FOR IMMERSION IN TANK OR DRUM, THE STRAINER WILL PASS THROUGH BUNG HOLE OF ANY STANDARD STEEL DRUM. LARGE OPEN AREA SCREEN PERMITS HIGH VOLUME LIQUID WITHDRAWAL WITH LITTLE CHANCE OF CLOGGING AND WITH MINIMUM PRESSURE LOSS THROUGH STRAINER.

AVAILABLE IN ALUMINUM WITH MONEL SCREEN.



LIQUID CAN BE WITHDRAWN TO WITHIN 1/4" OF DRUM OR TANK BOTTOM WITH STRAINER IN EITHER VERTICAL OR HORIZONTAL POSITION. STRAINER IS QUICKLY ATTACHED TO A HOSE. STRAINER IS EASILY DISASSEMBLED FOR CLEANING. REMOVAL OF KNURLED SCREW IN STRAINER BOTTOM RELEASES ALL PARTS. NO TOOLS NEEDED.

SCREEN DATA		
MESH SIZE	GROSS AREA (SQUARE INCHES)	OPEN AREA (SQUARE INCHES)
50 MESH MONEL	44.7	16.5
100 MESH MONEL	44.7	14.7

DESCRIPTION:  
NO. 8060  
SUCTION STRAINER



**Spraying Systems Co.**  
Spray Nozzles and Accessories  
P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.  
Ref.

Data Sheet No.  
**8060**  
SHEET OF