



DIAPH. PRESS. RELIEF VALVE NO.	INLET CONNECTION	BY-PASS CONNECTION	GAUGE CONNECTION	RECOMMENDED PRESS. RANGE
8460-1/2-50	1/2" N.P.T. (M)	1/2" N.P.T. (F)	1/2" N.P.T. (F)	UP TO 50 P.S.I.
8460-3/4-50	3/4" N.P.T. (M)	3/4" N.P.T. (F)	1/2" N.P.T. (F)	UP TO 50 P.S.I.
8460-1/2	1/2" N.P.T. (M)	1/2" N.P.T. (F)	1/2" N.P.T. (F)	UP TO 300 P.S.I.
8460-3/4	3/4" N.P.T. (M)	3/4" N.P.T. (F)	1/2" N.P.T. (F)	UP TO 300 P.S.I.

- TO MAINTAIN SELECTED PRESSURE FOR UNIFORM SPRAY BOOM OR BROADCAST SPRAYING.
- SUPERIOR DIAPHRAGM TYPE DESIGN FOR RESPONSIVE, CHATTER-FREE, PRESSURE CONTROL.
- PARTS TOUCHED BY CHEMICALS MADE OF NYLON OR STAINLESS STEEL -- WITH DIAPHRAGM OF SPECIAL CORROSION RESISTANCE.
- MAXIMUM CORROSION RESISTANCE TO ALL FARM CHEMICALS AND FERTILIZER SOLUTIONS.
- PRESSURE SETTING LOCKS IN POSITION.
- CONTROL PARTS ARE SEALED FROM LIQUID CONTACT.
- STAINLESS STEEL VALVE LINER.

NOTE

CAN BE USED WITH TEE VALVE - SEE BULLETIN #158.
 CAN BE USED WITH DIRECT VALVE - SEE BULLETIN #100.

FOR COMPLETE INFORMATION ON #8460 - DIAPHRAGM PRESSURE RELIEF VALVE, SEE BULLETIN NO. 191.

WEIGHT -- 14 OUNCES

DESCRIPTION:
 NO. 8460-1/2- & NO. 8460-3/4
 DIAPHRAGM PRESSURE
 RELIEF VALVE



Spraying Systems Co.[®]
 Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No. 1	Data Sheet No.
Ref.	8460
	SHEET OF