



AMP SuperSeal Connector  
34 Pos. w/ Skts

Pos.	Color	Function
1	Plug	(+12v) V Out Switched
2	Plug	ISO CAN Ground
3	Plug	ISO CAN H
4	Plug	ISO CAN H
5	Plug	ISO CAN L
6	Plug	ISO CAN L
7	Plug	DIAG Ground
8	Plug	DIAG RX
9	Plug	DIAG TX
10	Plug	(+12v) V Out Switched
11	Plug	TJ CAN Ground
12	Plug	TJ CAN H
13	Plug	TJ CAN H
14	Plug	TJ CAN L
15	Plug	TJ CAN L
16	Plug	GNSS In RX
17	Plug	GNSS In TX
18	Blk	Ground
19	Plug	IGN Sense In
20	Plug	Reverse Sense In
21	Plug	Status Sense In
22	Plug	GNSS Ground
23	Plug	3rd Party GND (not available)
24	Plug	3rd Party RX (not available)
25	Plug	3rd Party TX (not available)
26	Red	(+12v) Volts In
27	Plug	(+12) Volts Out
28	Plug	Ground
29	Plug	Ground
30	Plug	Speed Out (GS)
31	Plug	Ground (GS)
32	Plug	Debug GND (not available)
33	Plug	Debug RX (not available)
34	Plug	Debug TX (not available)



Connet +12v  
Cobo Connector

Pos	Color	Function
(+)	Red	(+12 volts) In
(-)	Black	Ground



MATERIAL:		n/a			
FINISH:		n/a			
PROJECTION:		SCALE: UNITS:		TITLE: Harness, 908 NAV, POWER w/COBO	
UNLESS OTHERWISE SPECIFIED TOLERANCE:		1:2		APPROVED BY: <i>Roy Sherida</i>	
R1 8/4/21 Updated		0.1" ±.1" 10:60" ±.1" 3XX		DRAWN BY: <i>Bryan Reiser</i>	
R0 3/30/21 Released		1.5" ±.25" 60:120" ±.2" 3XX		SHEET No: 1 of 1	
REV. DATE NOC. No		5:10" ±.5" 120" ±.3" 3XX		DWG No: C-45-10227	