



AMP SuperSeal Connector  
34 Pos. w/ Skts

Pos.	Color	Function
1	Plug	(+12v) V Out Switched
2	Plug	ISO CAN Ground
3	Plug	ISO CAN H
4	Plug	ISO CAN H
5	Plug	ISO CAN L
6	Plug	ISO CAN L
7	Plug	DIAG Ground
8	Plug	DIAG RX
9	Plug	DIAG TX
10	Plug	(+12v) V Out Switched
11	Plug	TJ CAN Ground
12	Plug	TJ CAN H
13	Plug	TJ CAN H
14	Plug	TJ CAN L
15	Plug	TJ CAN L
16	Orange	GNSS In RX
17	Red	GNSS In TX
18	Blk	Ground
19	Plug	IGN Sense In
20	Plug	Reverse Sense In
21	Plug	Status Sense In
22	Green	GNSS Ground
23	Plug	3rd Party GND (not available)
24	Plug	3rd Party RX (not available)
25	Plug	3rd Party TX (not available)
26	Red	(+12v) Volts In
27	Plug	(+12v) Volts Out
28	Plug	Ground
29	Plug	Ground
30	Plug	Speed Out (GS)
31	Plug	Ground (GS)
32	Plug	Debug GND (not available)
33	Plug	Debug RX (not available)
34	Plug	Debug TX (not available)




Connet +12v  
Cobo Connector

Pos	Color	Function
(+)	Red	(+12 volts) In
(-)	Black	Ground



GNSS  
DB9 SKT Connector

Pos.	Color	Function
1	n/a	
2	Red	GNSS In TX
3	Orange	GNSS In RX
4	n/a	
5	Green	GNSS Ground
6	n/a	
7	n/a	
8	n/a	
9	n/a	



MATERIAL:		n/a			
FINISH:		n/a			
PROJECTION:		SCALE: UNITS:		TITLE:	
				Harness, 908 NAV, POWER w/COBO, NO RCVR	
REV. DATE		NO. No		APPROVED BY: <i>Roy Shveda</i>	
R1 8/4/21 Updated		R0 4/28/21 Released		CHECKED BY: <i>Greg Dool</i>	
UNLESS OTHERWISE SPECIFIED TOLERANCE:		DRAWN BY: <i>Bryan Reiser</i>		SHEET No: <b>1 of 1</b>	
0-.1" ±.1"    10-60" ±.1"    .XX 1-.5" ±.25"    60-120" ±.2"    .XXX 5-10" ±.5"    120" ±.5"    .X		10-60" ±.1"    .XX 60-120" ±.2"    .XXX 120" ±.5"    .X		DWTG No: <b>C-45-10229</b>	

This drawing is the sole and exclusive property of TeeJet Technologies. This license is for use only by the Licensee and only in connection with an accompanying request for proposal or purchase order. This drawing is not to be reproduced, copied, distributed, displayed or otherwise disposed of, directly or indirectly by the Licensee, except upon the express consent of TeeJet Technologies.