



**AMP SuperSeal Connector
34 Pos. w/ Skts**

Pos.	Color	Function
1	Red	(+12v) V Out Switched
2	Black	ISO CAN Ground
3	White	ISO CAN H
4	Yellow	ISO CAN H
5	Green	ISO CAN L
6	Blue	ISO CAN L
7	Plug	DIAG Ground
8	Plug	DIAG RX
9	Plug	DIAG TX
10	Red	(+12v) V Out Switched
11	Black	TJ CAN Ground
12	Yellow	TJ CAN H
13	White	TJ CAN H
14	Green	TJ CAN L
15	Blue	TJ CAN L
16	Orange	GNSS In RX
17	Red	GNSS In TX
18	Plug	Ground
19	Plug	IGN Sense In
20	Black	Reverse Sense In
21	Black	Status Sense In
22	Green	GNSS Ground
23	Plug	3rd Party GND (not available)
24	Plug	3rd Party RX (not available)
25	Plug	3rd Party TX (not available)
26	Purple	ISO CAN (+12v) V In
27	Plug	(+12v) 3 AMP V Out Sw itched ButtSplice
28	Plug	Ground
29	Plug	Ground
30	Plug	Speed Out (GS)
31	Plug	Ground (GS)
32	Plug	Debug GND (not available)
33	Plug	Debug RX (not available)
34	Plug	Debug TX (not available)




**TeeJet CAN
Deutsch (DTM) 6 Pos**

Pos.	Color	Function
1	Red	(+12v) V Out Switched
2	Black	Ground
3	White	TJ CAN H
4	Green	TJ CAN L
5	Yellow	TJ CAN H
6	Blue	TJ CAN L



**GNSS
DB9 SKT Connector**

Pos.	Color	Function
1	n/a	
2	Red	GNSS In TX
3	Orange	GNSS In RX
4	n/a	
5	Green	GNSS Ground
6	n/a	
7	n/a	
8	n/a	
9	n/a	




**Reverse Sense
Spade Terminal Female**

Color	Function
Orange	Reverse Sense

**ISO CAN
9 pos SKT AMP**

Pos.	Color	Function
1	Red	(+12v) V Out Switched
2	Green	ISO CAN L
3	Blue	ISO CAN L
4	White	ISO CAN H
5	Yellow	ISO CAN H
6	n/a	
7	Purple	(+12v) V In
8	n/a	
9	Black	Ground



MATERIAL:		n/a			
FINISH:		n/a			
PROJECTION:		SCALE: UNITS:		TITLE: HARNESS, 908-ISO-TJD-G-RS	
UNLESS OTHERWISE SPECIFIED TOLERANCE:		1:2		APPROVED BY: <i>Roy Siroda</i>	
REV. DATE		NOC. No		CHECKED BY: <i>Greg Root</i>	
R1 4/14/22 000106		0-1" ±.1" 10-60" ±.1" 3X		DRAWN BY: <i>Bryan Reiser</i>	
R0 6/24/21 Released		1.5" ±.25" 60-120" ±.2" 300X		SHEET No: <i>1 of 1</i>	
		5-10" ±.5" 120" ±.5" 3X		DWG No: C-45-10234	