



**AMP SuperSeal Connector  
34 Pos. w/ Skts**

Pos.	Color	Function
1	Plug	(+12v) V Out Switched
2	Plug	ISO CAN Ground
3	Plug	ISO CAN H
4	Plug	ISO CAN H
5	Plug	ISO CAN L
6	Plug	ISO CAN L
7	Plug	DIAG Ground
8	Plug	DIAG RX
9	Plug	DIAG TX
10	Red	TJ CAN (+12v)
11	Black	TJ CAN Ground
12	Yellow	TJ CAN H
13	White	TJ CAN H
14	Green	TJ CAN L
15	Blue	TJ CAN L
16	Plug	GNSS In RX
17	Plug	GNSS In TX
18	Black	Ground
19	Plug	IGN Sense In
20	Black	Reverse Sense In
21	White	Status Sense In
22	Plug	GNSS Ground
23	Plug	3rd Party GND (not available)
24	Plug	3rd Party RX (not available)
25	Plug	3rd Party TX (not available)
26	Red	ISO CAN (+12v) V In
27	Red	(+12v) Switched V Out
28	Plug	Ground
29	Plug	Ground
30	Red	Speed Out (GS)
31	Black	Ground (GS)
32	Plug	Debug GND (not available)
33	Plug	Debug RX (not available)
34	Plug	Debug TX (not available)



**Ground Speed  
AMP 4 Pos Pin**


Pos.	Color	Function
1	Black	Speed Out (GS)
2	Red	Ground (GS)
3	n/a	
4	n/a	



**Fuse Holder  
WeatherPack 2 Pos.  
10 Amp Fuse Blade Type**


**Power  
Weather-Pack  
2 Pos Shroud**

Pos	Color	Function
A	Red	(+12 volts) In
B	Black	Ground



**TeeJet CAN  
Deutsch (DTM) 6 Pos**

Pos.	Color	Function
1	Red	TJ CAN (+12v)
2	Black	Ground
3	White	TJ CAN H
4	Green	TJ CAN L
5	Yellow	TJ CAN H
6	Blue	TJ CAN L



**Reverse Sense  
Status Sense  
+12v Switched  
Spade Terminal Female**

Color	Function
Black	Reverse Sense In
White	Status Sense
Red	Switched (+12) Volts Out

MATERIAL: n/a		TeeJet TECHNOLOGIES	
FINISH: n/a		TITLE: Harness, 908-NAV-TJD-PWP-RS-SS-PO-SP	
PROJECTION:		SCALE: UNITS: 1:2 INCH: X METRIC: X	
UNLESS OTHERWISE SPECIFIED TOLERANCE:		APPROVED BY: <i>Roy Sveda</i>	
R2	3/7/23	Updated	CHECKED BY: <i>Greg Best</i>
R1	4/14/22	000106	DRAWN BY: <i>Bryan Reiser</i>
R0	7/14/21	Released	SHEET No: 1 of 1
REV.	DATE	NOC. No	DWG. No: C-45-10236