

A

B

C


D

1

2

3

4



Plug, 28 Pos. Skt Framatome

153.50

Receptacle 28 pos. Pin Framatome

- A-Grn/Blk/Wht
- B-Red/Blk/Wht
- C-Wht/Blk/Red
- D-Blk/Wht/Red
- E-Orn/Grn
- F-Red/Grn
- G-Blu/Red
- H-Orn/Red
- J-Wht/Red
- K-Blk/Red
- L-Blu/Wht
- M-N.C.
- N-Red/Wht
- P-Blk/Wht
- R-Blu/Blk
- S-Orn/Blk
- T-Grn/Blk
- U-Grn/Wht
- V-Red/Blk
- W-Wht
- X-Wht/Blk
- Y-N.C.
- Z-N.C.
- a-Orn
- b-Grn
- c-Blu
- d-Blk
- e-Red

- A-Grn/Blk/Wht
- B-Red/Blk/Wht
- C-Wht/Blk/Red
- D-Blk/Wht/Red
- E-Orn/Grn
- F-Red/Grn
- G-Blu/Red
- H-Orn/Red
- J-Wht/Red
- K-Blk/Red
- L-Blu/Wht
- M-N.C.
- N-Red/Wht
- P-Blk/Wht
- R-Blu/Blk
- S-Orn/Blk
- T-Grn/Blk
- U-Grn/Wht
- V-Red/Blk
- W-Wht
- X-Wht/Blk
- Y-N.C.
- Z-N.C.
- a-Orn
- b-Grn
- c-Blu
- d-Blk
- e-Red

NOTES:

1.0 CABLE:

CABLE, 18 CONDUCTOR, 25GA.
 DESCRIPTION:
 CONDUCTORS: STRANDED TINNED COPPER
 INSULATION: COLOR-CODED POLYVINYL CHLORIDE
 CONSTRUCTION: CONDUCTORS ARE CABLED
 JACKET: CHROME POLYVINYL CHLORIDE
 TEMPERATURE RANGE: 10 5 deg. C
 VOLTAGE RATING: 300 VOLTS
 UL STYLE 2464

MATERIAL: N/A		Midwest Technologies Illinois	
FINISH: N/A		TITLE: 48297-S5-4 Cable, Main Ext., 4 Meter	
PROJECTION:	SCALE: UNITS: X INCH METRIC: X	DRAWN BY: Bryan Reeves	
UNLESS OTHERWISE SPECIFIED TOLERANCE:		CHECKED BY: Bryan Reeves	
R0	7/17/02	010128	APPROVED BY: Bryan Reeves
REV.	DATE	DOC. No.	SHEET No: 1 of 1 DWG No: C-45-20240
Midwest Technologies IL, LLC. Claims proprietary right in the material disclosed hereon. This document is not to be used in any way detrimental to the interest of Midwest Technologies IL, LLC.			