



Features:

- Clear Bowl for easy visual inspection of screen.
- Polypropylene Head and Clear Nylon Bowl.
- Bowl easily removed by hand to clean screen.

Maximum Recommended Pressure: 150 PSI (10 bar) @ 100°F (38°C) Max.

STRAINER NO.	PIPE CONN. (F)	SCREENS*				NET WEIGHT	APPROX. FLOW RATE WITH 5 PSI (0.35 bar) PRESSURE DROP
		MESH SIZE	OPENING	COLOR CODE	FULL AREA		
AA122-1/2-NYC	1/2" NPT	16	.045" (1.1 mm)	None	7.7 Sq. In. (49.7 cm ²)	3 1/2 oz. (0.1 kg)	12 GPM (45 l/min)
AAB122-1/2-NYC	1/2" BSPT	30	.021" (0.53 mm)	Flame Red			
AA122-3/4-NYC	3/4" NPT	50	.011" (0.28 mm)	Gentian Blue	7.7 Sq. In. (49.7 cm ²)	3 1/2 oz. (0.1 kg)	16 GPM (60 l/min)
AAB-3/4-NYC	3/4" BSPT	80	.007" (0.18 mm)	Zinc Yellow			
		100	.006" (0.15 mm)	Traffic Green			

* 50, 80 and 100 mesh screens reinforced with polypropylene ribs.

Description:

No. AA_122-1/2-NYC &
No. AA_122-3/4-NYC
Liquid Strainers



Spraying Systems Co.®

Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, Il. 60187-7901

Rev. No. 2

Data Sheet No.

122-NYC

Ref.

Sheet Of