

NOTE: Screen can be easily removed for cleaning by removing the retaining clip and pulling the bowl and head apart


MAXIMUM RECOMMENDED PRESSURE: 215 PSI (15 bar) at Temp. 70°F (20°C)

| STRAINER No. | PIPE CONN. | SCREENS* | | | | Net WEIGHT | APPROX FLOW RATE WITH 5 PSI (0.35 bar) PRESSURE DROP |
|---------------|---------------|-----------|-----------------|---------------|---------------------------------------------|-----------------|------------------------------------------------------|
| | | MESH SIZE | OPENING | COLOR CODE | FULL AREA | | |
| AA122ML-QC-PP | Quick Connect | 50 | .011" (0.28 mm) | Gentian Blue | 7.7 in ² (49.7 cm ²) | 6 oz. (0.17 kg) | 18 GPM (68 l/min) |
| | | 80 | .007" (0.18 mm) | Zinc Yellow | 7.7 in ² (49.7 cm ²) | | |
| | | 100 | .006" (0.15 mm) | Traffic Green | 7.7 in ² (49.7 cm ²) | | |

* 50, 80, 100 Mesh Screens Reinforced With Polypropylene Ribs

DESCRIPTION:

NO. AA122ML-QC-PP
LIQUID STRAINER



Spraying Systems Co.[®]
Spray Nozzles and Accessories
P.O. Box 7900 - Wheaton, IL 60189-7900

REVISION NO.

REFERENCE:

DATA SHEET

DS122ML-QC-PP

SHEET: OF

DWG SIZE: A