



Max. Recommended Pressure: 20 PSI (14 bar) at Temp. 70°F (20°C).

STRAINER PART NO.*				MESH SIZE	COLOR CODE	OPENING	FULL AREA	
AAB126MLSC-F50-__-VI	50-Series Flange	1/2" BSPT	Polypropylene	30	Flame Red	.021" (0.53 mm)	6 GPM (23 l/min)	
AA126MLSC-3-__-VI	3/4" NPT	1/2" NPT	Polypropylene	50	Gentian Blue	.011" (0.28 mm)	17 Sq. In. (109 cm <sup>2</sup> )	6 GPM (23 l/min)
AAB126MLSC-3-__-VI	3/4" BSPT	1/2" BSPT	Polypropylene	80	Zinc Yellow	.007" (0.18 mm)		
AA126MLSC-4-__-VI	1" NPT	1/2" NPT	Polypropylene	100	None	.006" (0.15 mm)	17 Sq. In. (109 cm <sup>2</sup> )	6 GPM (23 l/min)
AAB126MLSC-4-__-VI	1" BSPT	1/2" BSPT	Polypropylene	200	None	.003" (0.08 mm)		

\*Specify - VI in part number for Viton® Gasket and O-Ring

**Description:**

No. AA\_126MLSC-3-\_\_,  
 No. AA\_126MLSC-4-\_\_ &  
 No. AA\_126MLSC-F50-\_\_  
 Self-Cleaning Line Strainers



**Spraying Systems Co.®**

Spray Nozzles and Accessories  
 P.O. Box 7900 - Wheaton, IL 60187-7901

Rev. No. 1	Data Sheet No.
Ref.	126MLSC-1-PP
	Sheet Of