



TYPICAL NOZZLE ASSEMBLY

FEATURES:

- USED WITH QUICK TEEJET® CAPS
- BODY AVAILABLE WITH SINGLE (LEFT OR RIGHT) OR DOUBLE 3/8" PUSH-TO-CONNECT INLET
- WETTED COMPONENTS CONSIST OF NYLON, STAINLESS STEEL, POLYPROPYLENE, FKM & EPDM
- DRIP FREE POSITIVE SHUT-OFF (10 PSI STANDARD CHECK VALVE)
- BRASS RETAINING NUT FOR EASY MOUNTING
- MAXIMUM OPERATING PRESSURE 100 PSI (7 bar)

FLOW RATES (GPM) AT PRESSURE DROP (PSI)

NOZZLE BODY	SINGLE INLET	DOUBLE INLET
5 PSI	3.3 GPM	4.1 GPM
10 PSI	4.6 GPM	5.8 GPM

STYLE	BODY No.	"A" DIM. (APPROX.)	"B" DIM. (APPROX.)	"C" DIM. (APPROX.)
SINGLE RIGHT	QJ39685-1R-3/8-NYB-VI	2.5" (64mm)	1.8" (46mm)	3.0" (76mm)
SINGLE LEFT	QJ39685-1L-3/8-NYB-VI	2.5" (64mm)	1.8" (46mm)	3.0" (76mm)
DOUBLE	QJ39685-2-3/8-NYB-VI	3.2" (81mm)	1.8" (46mm)	3.0" (76mm)

DESCRIPTION:

**QJ39685 SERIES
PTC DIAPHRAGM
CHECK VALVE**



REVISION NO.	1	Data Sheet No.	
REFERENCE:	06/06/24	DS39685-PTC	
SHEET:	1 OF 1	DWG SIZE:	A