













CONNECTOR CODES: TABLE ONE

2-PIN OR 3-PIN	<p>AMP MALE FASTON SPADE CONNECTOR</p> <p>NOTE: NO PIN-OUT CODE NEEDED WITH THIS CONNECTOR.</p>  <p>2-PIN = CODE A 3-PIN = CODE J</p>	<p>AMP FEMALE FASTON RECEPTACLE CONNECTOR</p> <p>NOTE: NO PIN-OUT CODE NEEDED WITH THIS CONNECTOR.</p>  <p>2-PIN = CODE B 3-PIN = CODE K</p>
	<p>AMP FEMALE MATE-N-LOK CONNECTOR (SEALED)</p>  <p>2-PIN = CODE C 3-PIN = CODE L</p>	<p>AMP MALE MATE-N-LOK CONNECTOR (SEALED)</p>  <p>2-PIN = CODE D 3-PIN = CODE M</p>
	<p>PACKARD ELECTRIC WEATHER PACK SHROUD CONNECTOR (SEALED)</p>  <p>2-PIN = CODE E 3-PIN = CODE O</p>	<p>PACKARD ELECTRIC WEATHER PACK TOWER CONNECTOR (SEALED)</p>  <p>2-PIN = CODE F 3-PIN = CODE P</p>
	<p>DEUTSCH DT FEMALE CONNECTOR (SEALED)</p>  <p>2-PIN = CODE G 3-PIN = CODE Q</p>	<p>DEUTSCH DT MALE CONNECTOR (SEALED)</p>  <p>2-PIN = CODE H 3-PIN = CODE R</p>
	<p>PACKARD ELECTRIC METRIPACK FEMALE CONNECTOR (SEALED)</p>  <p>4-PIN = CODE S</p>	<p>JST VH FEMALE CONNECTOR (SEALED)</p>  <p>2-PIN = CODE I 3-PIN = CODE T</p>
	<p>PACKARD ELECTRIC WEATHER PACK SHROUD CONNECTOR (SEALED)</p>  <p>4-PIN = CODE U</p>	<p>PACKARD ELECTRIC WEATHER PACK TOWER CONNECTOR (SEALED)</p>  <p>4-PIN = CODE V</p>
4-PIN		

WIRING CODES: TABLE TWO

WIRING CODE

CODE LETTER	CONNECTOR POSITION			
	A OR 1	B OR 2	C OR 3	D OR 4
A	R	W	P	B
B	R	W	B	P
C	R	B	W	P
D	R	B	P	W
E	R	P	W	B
F	R	P	B	W
G	W	R	B	P
H	W	R	P	B
I	W	P	R	B
J	W	P	B	R
K	W	B	R	P
L	W	B	P	R
M	P	R	W	B
N	P	R	B	W
O	P	W	R	B
P	P	W	B	R
Q	P	B	R	W
R	P	B	W	R
S	B	R	W	P
T	B	R	P	W
U	B	W	R	P
V	B	W	P	R
W	B	P	R	W
X	B	P	W	R

WIRING CODE KEY:
 R=RED
 W=WHITE
 P=PLUGGED
 B=BLACK

DESCRIPTION:
**58480 MINI-DIN CABLE FOR
 e-CHEMSAVER™ AND 430
 ELECTRIC BALL VALVE**



Spraying Systems Co.®

Spray Nozzles and Accessories
 P.O. Box 7900 - Wheaton, Il. 60189-7900

Rev. No.

Ref.

DATA SHEET

DS58480

SHEET 2 OF 2