



ADAPTER No.	INLET CONN.	OUTLET CONN.	MATERIAL	MAXIMUM RECOMMENDED PRESSURE	"A"	"B" HEX.
7599-1/4-ENP	1/4" NPT (F)	1/4" NPS (F)	ELECTROLESS-NICKEL PLATED	1000 PSI (69 bar)	13/16" (20.6 mm)	5/8" (15.9 mm)
7599-3/8-ENP	3/8" NPT (F)	3/8" NPS (F)			59/64" (23.4 mm)	13/16" (20.6 mm)
7599-1/4-SS	1/4" NPT (F)	1/4" NPS (F)	STAINLESS STEEL	2000 PSI (138 bar)	13/16" (20.6 mm)	5/8" (15.9 mm)
7599-3/8-SS	3/8" NPT (F)	3/8" NPS (F)			59/64" (23.4 mm)	13/16" (20.6 mm)

THE No. 7599---ADAPTER MAY BE USED TO CONVERT A 1/4" NPS (M) HOSE THREAD CONNECTION TO 1/4" OR 3/8" NPT (F) PIPE THREAD CONNECTION.

ADAPTER MAY BE USED FOR: No. AA23, AA27, AA31 GUNJET® SPRAY GUNS AND No. AA22AUH AUTOJET® SPRAY GUN OR IN STAINLESS STEEL MATERIAL WITH No. AA24AUA AUTOJET® SPRAY GUN.

**DESCRIPTION:**

**NO. 7599--- ADAPTER FOR NO. AA23, AA27, AA31 GUNJET AA22AUH AND AA24AUA AUTOJET SPRAY GUNS**



**Spraying Systems Co.®**

**Spray Nozzles and Accessories  
P.O. Box 7900 - Wheaton, Il. 60189-7900**

Rev. No. 1

Ref.

DATA SHEET

**DS7599**

SHEET OF